Federal Permit No.: KSR410017

KANSAS WATER POLLUTION CONTROL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) PERMIT AND AUTHORIZATION TO DISCHARGE UNDER THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM

Pursuant to the provisions of Kansas Statutes Annotated 65-164 and 65-165, the Federal Water Pollution Control Act as amended, 33 U.S.C. 1251 et seq., the "Act",

Permittee: Maize, City of

Permittee's Address: P.O. Box 245 Maize, KS 67101

Drainage Basin: Lower Arkansas River

County: Sedgwick

is hereby authorized to discharge stormwater from the municipal separate storm sewer system (MS4) as described herein in accordance with the limitations, conditions and requirements set forth in this permit.

This permit is effective <u>December 1, 2019</u>, supersedes the previously issued MS4 general permit M-AR58-SU01 and expires November 30, 2024.

PERMIT AREA AND AUTHORIZED DISCHARGES

This permit covers all areas within the permittee's MS4 jurisdiction which are also located in the urbanized area as defined by the 2010 U.S. Census (the Permit Area). The Permit Area may change based upon areas incorporated into or removed from the permittee's jurisdictional area during the term of this permit.

This permit authorizes the discharge of all existing or new stormwater point source discharges from the Municipal Separate Storm Sewer System (MS4) located within the Permit Area. New stormwater discharges are those which are created and/or incorporated into the permittee's MS4 during the term of this permit.

Lee a. norman mo

Secretary, Kansas Department of Health and Environment

November 27, 2019 Date

PART I. STORMWATER MANAGEMENT PROGRAM (SMP) DOCUMENT REQUIREMENTS

A. Current Stormwater Management Program

The permittee shall continue to implement and enforce the current Stormwater Management Program (SMP), as documented in the SMP document, until an updated SMP is implemented. Revised or modified surface water monitoring may be implemented in 2019 as allowed and if so required by this permit.

Any updated SMP shall be designed to:

- 1. Reduce the discharge of pollutants from the municipal separate storm sewer system (MS4) to the Maximum Extent Practicable (MEP),
- 2. Continue to implement the six minimum control measures as listed in PART I Section C,
- 3. Satisfy the requirements of this permit, the Clean Water Act and Kansas surface water quality statutes and regulations.

Implementation of Best Management Practices (BMPs) consistent with the provisions of the SMP document and this permit constitutes compliance with the standard of reducing pollutants to the Maximum Extent Practicable.

B. Updated Stormwater Management Program document

The SMP shall be updated and submitted to KDHE between January 1 and February 28 of 2021 (submitted with the Annual Report and the updated SMP must be effective in 2021). As this permit imposes additional requirements for implementation of BMPs and/or surface water monitoring [see PART II. Total Maximum Daily Load (TMDL) Best Management Practices and Surface Water Monitoring] beyond what the previous permit imposed, the current SMP shall be modified with the SMP document updated to include the additional requirements imposed by this permit. Some specific requirements for updating the SMP document are addressed in PART I Section D. "Total Maximum Daily Load (TMDL) Regulated Pollutants." Additionally, to comply with new EPA regulations [National Pollutant Discharge Elimination System (NPDES) Municipal Separate Storm Sewer System General Permit Remand Rule (Remand Rule)], as finalized and effective January 9, 2017, this permit must include requirements in clear, specific, and measurable terms. Tables of BMPs are listed along with point values, and the permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year beginning in 2021. The Remand Rule was published on December 9, 2016 in the Federal Register, Vol. 81, No. 237 beginning on page 89320.

This rule clarifies that terms and conditions must be expressed in terms which are "clear, specific, and measurable." The permit requirements must be enforceable and must provide a set of performance expectations and schedules readily understood by the permittee, the public, and the permitting authority alike. To provide as much flexibility to the permittee in implementing their stormwater management program in compliance with this permit and the Remand Rule, KDHE has elected to establish a point system and a list of various BMPs, tasks, or other conditions with associated point values to be tallied and demonstrate compliance with the total point requirement for each of the Six Minimum Control Measures and TMDL BMPs when required.

Modification of the SMP is permitted as the need arises. Modifications can be accomplished with any of the following methods:

- 1. Normally the SMP document is updated near the end of the calendar year and submitted to KDHE for review along with the annual report which is due after the first of the calendar year but before the 28th of February. In this case the permittee can begin implementation of the new SMP as soon as they have submitted the SMP to KDHE. The permittee is required to implement the SMP, which was most recently submitted to KDHE along with the annual report, throughout the entire year and may continue to implement the updated SMP until subsequently modified. The updated SMP as submitted must be approved by KDHE. If KDHE finds the SMP is not approvable, requirements for modification and resubmittal will be addressed to the permittee.
- 2. If it becomes necessary to modify the SMP at some time other than when the annual report is submitted to KDHE, the permittee may make the modifications to the SMP document and submit the SMP document to KDHE for approval. The permittee shall not begin implementation of the modified SMP until after KDHE has provided approval. KDHE may provide full approval of the modified SMP, or may provide conditional approval, may require revision of the modified SMP document and resubmission for subsequent review or may elect to not approve the modified SMP.
- 3. KDHE may require the permittee modify the SMP at any time, requirements for modification and resubmittal will be addressed to the permittee

C. Six Minimum Control Measures

The Permittee shall continue to review, update and implement BMPs with measurable goals for each of the six minimum control measures. The six minimum control measures and requirements are as follows:

1. Public Education and Outreach

The permittee shall continue to implement a public education program which includes distribution of educational materials to the community or conducting equivalent outreach activities which address the impacts of stormwater discharges on water bodies and the steps the public can take to reduce pollutants in stormwater runoff.

a. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 4 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 7 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings or public forums; a single public hearing or forum can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Public Education and Outreach program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp P Ed & O - 01			
Maintain a stormwater webpage for the permittee.	Maintain the webpage with up to date information with all links effective and valid information. Check all links and update website as necessary on a minimum monthly basis. Document monthly checks in log book and indicate changes with logged summaries.	The webpage must be available throughout the year once it is posted and initially made available. In the initial year posted it must be available for a minimum of 3 months to qualify for the points. In subsequent calendar years the points may be claimed if the webpage has been maintained throughout the twelve months.	3 points may be claimed in the first year implemented, and 2 points may be claimed for each successive year the webpage is maintained available.
Lbmp P Ed & O - 02 Distribute educational materials (either flyers, brochures, catalog mailings, handouts, or e-mails) addressing various pertinent stormwater	Number of all flyers, brochures, catalog mailings, handouts, or e-mails distributed in a year shall equal or exceed the most recent U.S.	Either flyers, brochures, catalog mailings, handouts, or e-mails are to be distributed in at least two separate batches,	2 points may be claimed in a year in
public education topics.	Census Bureau decennial housing units value for the permit area. The applicable U.S. Census housing units value shall be documented, and the number of flyers, brochures, or e-mails distributed shall also be documented. This information and copies of the flyers, brochures, or e-mails shall be retained on file.	ideally in separate seasons (either winter, spring, summer or fall). However, the required number of flyers, brochures, or e-mails must be distributed in a single calendar year and the points can be claimed for that year.	which the required number of flyers, brochures, catalog mailings, handouts, or e-mails are distributed.
Lbmp P Ed & O - 03			2 points may be claimed in any year in
Provide either training or educational materials to permittee identified businesses at high risk of contributing to stormwater pollution.	Training or educational materials must be provided, within the year, to at least five separate businesses	The required amount of training or distribution of educational materials must occur within the	which the required amount of training or distribution of educational

Kansas Permit No.: M-AR58-SU01 Page 5 of 57

C 1. 1.			
Such businesses can	if the population of	year for which	material
include, but are not	the municipality is	points are claimed.	occurs.
limited to, food	greater than 10,000,		
service, auto service,	or three businesses		
disaster response and	if the population of		
janitorial services. The	the municipality is		
training or educational	between 3,000 and		
materials shall address	9,999, or two		
best management	separate businesses		
practices they can	if the population of		
employ to minimize or	the municipality is		
avoid adverse stormwater	less than 3,000.		
impacts due to their			
operations.	There is no		
	requirement to		
	provide training to		
	business in separate		
	business categories,		
	although it is		
	allowed.		
Lbmp P Ed & O - 04			
			2 points may
			be claimed in
Apply notification,	Apply this	The required number	years when the
placard, covers/hatches	notification on at	of placards,	required
with message, or	least 10% of all	covers/hatches with	number of
stencil, on stormwater	known stormwater	message, or	inlets (10%)
inlets to provide a	inlets in the MS4.	stencils must be	receive
message similar to "No		placed within the	placards,
Dumping - Drains to		year for which	covers/hatches
River"		points are claimed.	with message,
		Alternately, points	or stencils or
		may be claimed in	in subsequent
		any subsequent year	years when an
		when an additional	additional 5%
		5% of all known	of all known
		stormwater inlets	stormwater
		in the MS4 bear the	inlets in the
		placard,	MS4 bear the
		covers/hatches with	placard,
		message, or	covers/hatches
		stencil.	with message,
			or stencil.
Lbmp P Ed & O - 05			
Post the municipality's	The two documents	Months for which	1 point may be
MS4 permit and SMP	must be posted for at	the posting occurs	claimed for
document on either the	least six months of	must be within the	posting each
stormwater web page or	the year to claim one	year for which	year (minimum
the municipal webpage.	point.	points are claimed.	of at least
· · · · · · · ·		No "carryover" of	six months).
		months from one	
		year to the next.	
Lbmp P Ed & O - 06		year to the next.	2 204-4-
			2 points may
			be claimed
	1		for each year
Provide either a	Respond to all	The	
Provide either a stormwater telephone	Respond to all	The hotling (reporting	the hotline /
Provide either a stormwater telephone hotline or web based or	Respond to all reported complaints within 10 days and,	The hotline/reporting system must be	

text message method for	if found valid,	available to the	maintained and
public reporting of	resolve or establish	public for at least	available. An
illicit discharges.	a schedule for	six months in the	additional
	resolution within 20	year to claim the	point may be
	days. Actual	points.	claimed for
	resolution may take		each illicit
	more than 20 days,		discharge
	but the schedule for		resolved in
	resolution must be		the year up to
	finalized and the		a limit of 2
	efforts to implement		additional
	resolution must begin		points per
	within 20 days		year. One
	following receipt of		point allowed
	complaint. Document		per illicit
	complaints and		discharge
	response/resolution process for all		resolved.
	complaints received		
	in the year.		
	in the year.		
	Resolution of an		
	illicit discharge can		
	include, but is not		
	limited to;		
	elimination of the		
	discharge; on-site		
	treatment to allow		
	discharge to the MS4		
	(normally requires an		
	NPDES permit);		
	redirecting the		
	discharge to a		
	location that the		
	discharge is not		
	considered illicit, i.e., sanitary sewer		
	_		
	or to holding tanks to allow the waste to		
	be hauled off for		
	appropriate		
	treatment,		
	reuse/recycle or		
	disposal.		
Lbmp P Ed & O - 07			
Provide educational	Identify and educate	All the	3 points may
material annually to at	at least 4	requirements for	be claimed
least four groups,	groups/entities from	sending educational	each year this
including each of the	the listed types	material to the	BMP is
following types:	annually developing	various groups must	implemented in
Residents,	topics that are group	occur in a single	compliance
Businesses/Institutions,	specific and address	year to qualify for	with the
Commercial	activities and or	the points in that	specified
entities/Developers, and Industrial facilities.	그렇지? 전철 방법을 통하는 것을 하는 것을 다 가지 않는 것을 하는 것을 하는 것을 하는 것을 하는 것을 하는 것을 수 있다.	year.	requirements.
The educational material	concern.		
may be provided as any			
of the following:			
or the rorrowrind:			

Kansas Permit No.: M-AR58-SU01 Page 7 of 57

 > Brochures > Flyers > E-mails > Press release 			
Provide stormwater education for students at a school campus within K-12 (those grades present at the campus) within the permittee's jurisdiction or within 30 miles from this permit area. The training may be limited to the individual campus (local school buildings associated with a single address). This training does not need to be provided to the entire school system, e.g., USD. Alternately, funding stormwater BMP installations and/or field trips at the school campus will qualify.	<pre>Provide or fund an educator or speaker that will reach at least 5% of the K-12 students as normally attend school in the selected school campus. Alternately, the funding of BMPs at the school campus may provide for any of the following: > Installation of BMPs at the school > stormwater related field trips > water quality stream sampling activities > construction of rain gardens on school property > rain barrel workshops > rain garden workshops</pre>	All of the required students (5% minimum) in K-12 at the selected campus must be educated in a single year to qualify for the points in that year. Alternately, stormwater BMPs may be funded at a school campus where students may participate in installation or observe operation of the BMPs. Any of the items listed under measurable goals qualify.	3 points may be claimed each year this BMP is implemented in compliance with the specified requirements (provide education and/or fund stormwater BMP installations at the school campus).
<pre>Lbmp P Ed & O - 09 1. Operate an information booth at a large public event, (such as a sports event, fair, or music festival) where at least an estimated 1,000 or more individuals attend. 2. Alternately, operate an information booth</pre>	Provide information about stormwater topics of current interest.	All events shall have the booth staffed by the permittee for at least 50% of the days the event occurs.	2 points may be claimed each year this BMP is implemented in compliance with the specified requirements for alternative 1. (1,000 or more attendees) or alternative 2. (3,000 attendees).

Kansas Permit No.: M-AR58-SU01 Page 8 of 57

<pre>at multiple public events, (such as a sports event, fair, or music festival) where a cumulative estimated total of 3,000 or more individuals attend.</pre> 3. And finally, a single point can be claimed for operating an information both at a public event where at least an estimated 200 or more individuals attend.			Finally, 1 point may be claimed each year this BMP is implemented in compliance with the specified requirements for alternative 3(200 attendees).
Lbmp P Ed & O - 10			
Provide either training or educational materials to lawn/turf care service entities addressing best management practices they can employ to minimize or avoid adverse stormwater impacts due to their operations.	Training or educational materials must be provided, within the year, to at least five lawn/turf care service entities or at least 20% of the lawn care service entities located in the municipality whichever is least.	The required amount of training or distribution of educational materials must occur within the year for which points are claimed.	2 points may be claimed in any year in which the required amount of training or distribution of educational material occurs.
Lbmp P Ed & O - 11 Adopt a public education program to reduce littering.	Install and/or maintain signs to discourage littering. Signs are to be located in areas where littering has been a problem.	Credit can be claimed for any year in which signs are installed and in place for greater than six months or in cases where signs have previously been installed in any year where the signs remain posted for the full year.	<pre>1 point may be claimed for the year when signs are posted for six months or more, or 1 point may be claimed in subsequent years where the signs remain posted throughout the year.</pre>
Lbmp P Ed & O - 12 Create a stormwater information brochure to provide to the public at	Have multiple copies of the brochure available during at least 10 meetings or	The brochures shall address stormwater topics of concern.	<pre>1 point may be claimed in any year the brochures are made available to the public at meetings</pre>

Kansas Permit No.: M-AR58-SU01 Page 9 of 57

public meetings and/or	hearings open to the		and/or
hearings	public during the year. Provide the brochures to the		hearings as required.
	public at no charge.		
Lbmp P Ed & O - 13			
			1 point may be
Operate an adopt a highway program to utilize public volunteers to clean road right-of-way.	The volunteers shall clean at least a two- mile segment of road either within the permit area or	The road right-of- way shall be cleaned at least once per year. Points may be	claimed in any year a two- mile road segment is
	adjacent to the permit area. Alternately multiple spots (such as	claimed for any year in which cleaning has occurred.	cleaned or alternately multiple spots are cleaned
	roadways, parks, and waterways) which are cleaned and equate to	occurred.	which equate to or exceed a two-mile road clean-up.
Lbmp P Ed & O - 14	or exceed a two-mile road clean-up can qualify for a point.		
Hold a media campaign addressing various pertinent stormwater public education topics.	Estimated media exposure during prime-time broadcasting for the duration of the campaign shall be 10 times the most recent U.S. Census Bureau decennial population value for the permit area. The date, time, and estimated media exposure for each spot broadcast shall be documented and kept on file along with the applicable U.S. Census population value.	The media campaign shall be run within the year for which points are claimed. A new media campaign shall be run for each year points are claimed.	2 points may be claimed in a year in which the media campaign meeting the minimum exposure rate is conducted.
Develop or participate in an ongoing social media program on pertinent stormwater public education topics.	Publish or share social media content on the permittee's social media accounts at least six times per year. Record post topic, the number of impressions and engagement for each post. Include link to permittee's	The required number of social media posts must occur within the year for which the posts are claimed.	2 points can be claimed in a year which the required number of content is shared.

Kansas Permit No.: M-AR58-SU01 Page 10 of 57

	stormwater education website.		
Lbmp P Ed & O - 16 Operate an information booth at a public event or hold a public event which is intended to improve public understanding of issues related to water quality. The event may be associated with any environmental related issue including but not limited to an environmental expo, earth day, world wetlands day, international day of action for rivers, world fish migration day, world biodiversity day, world oceans day, world cleanup day, world water monitoring day, world rivers day, and America recycles day.	At least an estimated 800 or more individuals must attend the event.	The booth must be staffed at least 50% of the time the event is open to the public.	2 points may be claimed each year this BMP is implemented in compliance with the specified requirements. Municipal staff from multiple permittees may staff the both and claim points, for their municipality, for this BMP if their staff meet the 50% of the time staffing requirement.
Lbmp P Ed & O - 17 Operate an adopt a street program to utilize public volunteers to clean street right-of-way.	The volunteers shall clean at least a two- mile segment of street, either a single street or multiple streets, either within the permit area or adjacent to the permit area.	The street right- of-way shall be cleaned at least once per year. Points may be claimed for any year in which cleaning has occurred.	<pre>1 point may be claimed in any year at least two miles of street right- of-way is cleaned by volunteers.</pre>

- b. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Public Education and Outreach requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- c. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

2. Public Involvement/Participation

The permittee shall continue to implement a public involvement and participation program to solicit public comments and recommendations regarding the BMPs and measurable goals utilized by the permittee to comply with the permit. The permittee shall comply with State and local public notice requirements when implementing a public involvement and participation program.

a. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 3 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 6 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings or public forums; a single public hearing or public forums can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Public Involvement/Participation program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp P I/P - 01			
Hold a public hearing or public forum to notify the public about stormwater program activities and to solicit public comments regarding stormwater issues.	Provide public notice of the hearing/forum, invite local news media, either newspaper, radio or TV, and document the hearing with attendance sign-in sheet and minutes of the hearing which include public comments and responses.	Retain copies of the notices to public, invitations to attend, attendance sign-in sheets, and minutes. Points may be claimed in year which hearing is held.	2 points may be claimed each year this BMP is implemented in compliance with the specified requirements.
Lbmp P I/P - 02			
Establish a citizens advisory committee.	Host the citizens advisory committee meetings twice yearly and receive comments and guidance from the committee regarding the SMP. Retain on file copies of the attendance list and minutes of the meetings.	The citizens advisory committee must hold at least two meetings in the year which points are claimed.	3 points may be claimed each year this BMP is implemented in compliance with the specified requirements.

Kansas Permit No.: M-AR58-SU01 Page 12 of 57

Lbmp P I/P - 03			
Hold park or stream bank clean-up events for public volunteers to aid municipal staff in removing trash, debris, or pollutant sources from the selected clean-up area.	Clean an area which must be equal to or greater than one acre or alternately at least 200 yards of streambank. Alternately, for municipalities with less than 500 population clean an area which must be equal to or greater than a quarter of an acre or alternately at least 100 feet of streambank.	At least one such clean-up activity must occur in the year for which points are claimed.	3 points may be claimed each year this BMP is implemented in compliance with the specified requirements.
Train either citizen watch groups, homeowner associations (HOAs), or public service groups to recognize illicit discharge activities and communicate observations to appropriate municipal staff.	Provide training or distribute training materials to the group participants at least once annually.	At least one such training activity or distribution of training materials must be provided to the group in the year for which points are claimed.	2 points may be claimed each year this BMP is implemented in compliance with the specified requirements.
Lbmp P I/P - 05 Provide at least two events for residents to engage in cleanup activities and improve water quality in the municipality. Lbmp P I/P - 06	Provide at least two events in streams, streamside parks, areas adjacent to public waterways, and/or other green infrastructure/water resources. These events can be any of the following: Environmental restoration events, stream cleanups, tree plantings, or stream monitoring.	At least two events in compliance with the stated goals must be conducted within the year for which points are claimed.	3 points may be claimed each year this BMP is implemented in compliance with the specified requirements. 2 points may be claimed
Establish a program to encourage residents to install stormwater	Encouragement can include funding, grants, and other	One or more of the listed methods of encouragement must	each year this BMP is implemented in compliance

Kansas Permit No.: M-AR58-SU01 Page 13 of 57

treatment best management practices on their property.	financial incentives, trainings and or giveaways. Stormwater treatment BMPs can include: rain barrels, rain gardens, native plantings, native trees, cisterns and vegetated swales. Record participation numbers annually.	be implemented in the year for which points are claimed.	with the specified requirements, with the addition of 1 additional point (for a total of 3 points in the year) each year that participation increases 10% from the previous year.
Lbmp P I/P - 07 Enact either an ordinance, a resolution, or other enforceable requirement that requires pet owners or their keepers to immediately and properly dispose of their pet's solid waste deposited at parks or rest areas owned by the permittee.	The ordinance or resolution or other enforceable measure shall be enacted, and signs posted informing the public of their obligation at the park. The installation of a pet waste bag dispenser in the public area qualifies as adequate signage.	In the year the Measurable Goal requirement is implemented the point may be claimed and for each year thereafter.	<pre>1 point may be claimed for the year in which the Measurable Goal requirements are enacted, and 1 points may be claimed for each subsequent year the Measurable Goal requirements remain in effect.</pre>
Provide a monetary donation to a scholarship fund for students pursuing a degree in an environmental program which would qualify them to work in a field which can result in water pollution control.	A \$500 contribution in a year is the minimum acceptable amount to achieve this goal.	The donation must be made in the year the points are claimed.	2 points may be claimed each year this BMP goal is achieved.
Lbmp P I/P - 09 Distribute stormwater educational materials to the public within this permit area. Alternately, the permittee may provide	The educational materials, for each topic, which are distributed or supplied must have a value of at least \$50. Topics may be anything related to	For educational materials distributed or provided to nearby municipalities each year points may be claimed	<pre>1 point may be claimed per topic addressed in compliance with the requirements, up to a total of 5 points/topics.</pre>

Kansas Permit No.: M-AR58-SU01 Page 14 of 57

stormwater educational materials, e.g. brochures, flyers, or pamphlets. These materials may address various stormwater topics. For this alternative these materials may be provided to other nearby municipalities for distribution to the public. The nearby municipalities must be within 30 miles from this permit area.	stormwater including but not limited to clean-up guidance following flooding, discouraging littering, explaining and discouraging illicit discharges to the storm sewers, guidance on constructed BMPs for home owners (rain gardens, rain barrels, etc.) guidance on area household hazardous waste receiving centers, and guidance on area recycling programs.	when materials are provided with equal or greater value as required for each separate topic.	
Lbmp P I/P - 10 Establish a program to employ (either paid or unpaid) high school or college age environmental interns in an environmental related program including but not limited to either the wastewater utility, stormwater utility, potable water utility or solid waste utility.	The intern must receive the same environmental related training a new full-time employee would receive, within the first six months of the full-time employee's employment, during their internship.	The internship must last at least 8 weeks in the year when points are claimed.	2 points may be claimed each year this BMP goal is achieved per intern.

- b. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Public Involvement/Participation requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- c. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

3. Illicit Discharge Detection and Elimination

The permittee shall:

- a. Continue to implement and enforce a program to detect and eliminate illicit discharges into the MS4.
- b. Maintain a storm sewer system map of the permittee's MS4, showing the location of all outfalls, either pipes or open channel drainage, showing the names and location of all streams or lakes receiving discharges from those outfalls. A copy of the map shall be submitted to KDHE with the annual report if requested by KDHE. This map may be submitted as a PDF file(s) on a compact disk (CD) or a digital versatile disk (DVD).
- c. Implement and enforce an ordinance, a resolution, or other enforceable requirement, if the permittee has the authority to do so, to prohibit non-stormwater discharges into the storm sewer system and implement appropriate enforcement procedures and actions. A copy of the ordinance or resolution shall be submitted to KDHE with the annual report if requested by KDHE.
- d. Inform public employees, businesses, and the general public of hazards associated with illegal discharges and improper disposal of waste.
- e. Develop and implement a plan to detect/inspect for and address prohibited non-stormwater discharges, including illegal dumping, to the storm sewer system. The plan must include efforts to identify and evaluate dry weather MS4 discharges to detect and eliminate any associated illicit discharge. Unless identified by either the permittee or KDHE as a significant source of pollutants to waters of the state, several types of non-stormwater flow are not normally prohibited from entering the Municipal Separate Storm Sewer System:

Discharges which are not necessarily prohibited include:

- I. Water line flushing
- II. Diverted stream flows
- III. Rising ground waters
- IV. Uncontaminated groundwater infiltration as defined under 40 CFR 35.2005(20) to separate storm sewers
- V. Uncontaminated pumped groundwater
- VI. Contaminated groundwater if authorized by KDHE and approved by the municipality
- VII. Discharges from potable water sources
- VIII. Foundation drains
 - IX. Air conditioning condensation
 - X. Irrigation waters
 - XI. Springs
 - XII. Water from crawl space pumps

- XIII. Footing drains
- XIV. Lawn watering
- XV. Individual residential car washing
- XVI. Occasional not-for-profit car wash activities
- XVII. Flows from riparian habitats and wetlands
- XVIII. Dechlorinated swimming pool discharges excluding filter backwash
 - XIX. Street wash water (excluding street sweepings which have been removed from the street)
 - XX. Discharges or flows from firefighting activities
 - XXI. Heat pump discharge waters (residential only)
 - XXII. Treated wastewater meeting requirements of an NPDES permit
- XXIII. Sump pump drains
- XXIV. Other discharges determined not to be a significant source of pollutants to waters of the state, a public health hazard or a nuisance.
- f. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 5 points total on an annual basis for calendar years 2021 and 2022. The point total requirement increases to 7 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings or public forums; a single public hearing or public forums can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing an Illicit Discharge Detection and Elimination program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

Kansas Permit No.: M-AR58-SU01 Page 17 of 57

BMP Summary	Measurable Goal	Implementation Time Schedule	Points
Lbmp I D D & E - 01 Hold a public hearing or public forum to educate the public about illicit discharges and alternate acceptable methods of disposal or reuse of substances and/or materials. Lbmp I D D & E - 02	Provide public notice of the hearing/forum, invite local news media (either newspaper, radio or TV), and document the hearing with attendance sign-in sheet and minutes of the hearing which include questions/comments from the attendees and answers/comments from the permittee staff.	Retain copies of the notices to public, invitations to attend, attendance sign-in sheets, and minutes. Hearing must be held in year for which points are claimed.	2 points may be claimed for any year a hearing/forum is held.
<pre>Implement a program to abandon failed or failing residential or commercial on-site wastewater treatment facilities. These on- site wastewater treatment systems such as septic tank - lateral systems or lagoon systems are then connected to the municipal wastewater collection system for treatment of wastewater at the municipal wastewater treatment plant. Alternately, upgrade or replace the failed system to restore performance.</pre>	Redirect the wastewater generated by the facility to the municipal wastewater treatment collection system for proper treatment and disposal. Alternately, upgrade or replace the failed system with improvements which meet or exceed the present code or local requirements.	For each failed or failing on-site system which is abandoned, and the wastewater is redirected to the municipal wastewater treatment system, the permittee may claim points in the year the system is initially connected into the municipal wastewater treatment system. Alternately, for systems which are upgraded or replaced to restore adequate performance a lower number of points may be claimed in the year the upgrade or replacement is completed.	3 points may be claimed for each abandoned system in the year it is abandoned, alternately for systems which are upgraded or replaced as per the requirements a total of 2 points may be claimed in the year upgrade or replacement is completed.
Lbmp I D D & E - 03 Develop a spill response plan and, if appropriate, coordinate emergency	The plan shall include, at a minimum, explanation of appropriate spill	The plan may be implemented in any year and points claimed for the	3 points may be claimed in the year initially implemented, and

Kansas Permit No.: M-AR58-SU01 Page 18 of 57

response with other agencies or organizations.	response activities for spills associated with vehicle accidents, at grade or above ground storage tanks, and vehicle fluids from mechanical equipment such as construction equipment, cars, or trucks. The written plan shall be maintained on file.	initial implementation or for each year the plan remains effective.	2 points may be claimed for each successive year the plan remains effective.
Implement a program to evaluate MS4 outfalls to identify illicit discharges. Inspect at least 5% of the known MS4 outfalls during a calendar year and evaluate the ones which have dry weather discharges. Evaluate the water quality of the dry weather discharges to recognize non- stormwater contributions and trace the source of any illicit discharge.	When at least 5% of the known MS4 outfalls are inspected and for which at least one outfall was identified as discharging (entirely or partially) flow from an illicit discharge, the allotted points may be claimed in the year when the illicit discharge is eliminated. Document the MS4 outfalls inspected, the outfalls with dry weather discharges and the MS4 outfalls associated with illicit discharges.	The evaluation of a group of at least 5% of the known MS4 outfalls may be completed all in one year or may occur in up to two consecutive years and a point can be claimed. The larger number of points may be claimed only for the year in which the illicit discharge(s), associated with this group of evaluated outfalls is/are eliminated.	<pre>1 point may be claimed in the year when a total of at least 5% of the known MS4 outfalls are finally inspected, and 2 additional points may be claimed in which the illicit discharge(s), associated with this group of evaluated outfalls is/are eliminated.</pre>
Lbmp I D D & E - 05 Distribute a letter (or flier) and/or e- mail along with a press release from a municipal official with the intent of reaching every resident and business in the MS4 permit area. The distributed documents shall provide information on how to avoid illicit discharges to the MS4, i.e., proper disposal methods for common substances or materials often discharged illicitly. Provide a link to the	The letter (or flier) and/or e-mail along with the press release shall highlight the requirements for proper disposal of wastes and disposal methods. Copies of these documents shall be retained on file along with the distribution/mailing lists to document distribution to the target area (minimum MS4 permit area) to avoid illicit discharges to the MS4. Provide a link to the municipal website	The distribution of these various documents, letter (or flier) and/or e-mail along with the press release, shall all occur in the same month. Permittee may claim these points in the year these documents are distributed.	

Kansas Permit No.: M-AR58-SU01 Page 19 of 57

municipal website	where applicable		
where applicable	ordinances and		
ordinances and disposal guidance are	disposal guidance are posted.		
posted.	posteu.		
Lbmp I D D & E - 06			
Inspect, by televising pipelines or direct visualization of open channel drainage, 2% of the MS4 system within the permit area all conducted within a 12-month period to aid in identifying illicit discharges as well as evaluate the condition of the storm sewer lines/drainage channels-ditches. If in a 12-month period 10% of the MS4 system is inspected a higher point value may be claimed.	Generate a summary report of the inspection including the number of linear feet televised, number of linear feet visually inspected, condition comments, illicit discharges identified and the results of efforts to eliminate illicit discharges, e.g., discharge line disconnected and redirected to the sanitary sewer or discharge practice terminated.	The inspection process can occur in a single calendar year or may be conducted over a period extending from one year into the succeeding year. Points may be claimed in the year when the televised and/or visual inspection of this portion of the MS4 system (either 2% or 10%) is completed.	3 points may be claimed for inspection of 2% of the MS4 system, alternately if 10% of the MS4 system is inspected 5 points may be claimed.
Lbmp I D D & E - 07			
Implement a Household Hazardous Waste Collection Program (HHWCP) or document others have implemented such a program to provide such service to all property owners or residents located within the permit area. Lbmp I D D & E - 08	Document the residents and property owners within the MS4 permit area were able to dispose of such wastes at the HHWCP during a calendar year. Retain this documentation on file.	The property owners or residents located within the permit area must be able to dispose of waste accepted by the HHWCP throughout a calendar year. Points may be claimed for any such year.	3 points may be claimed for any year in which this BMP was implemented in compliance with the requirements.
א מ מ ד לייים			5 points may be claimed
Implement a program to increase the reliability of sanitary sewer pump stations above the minimum standard design requirements.	<pre>A pump station shall be upgraded to include the following:</pre>	In the year all improvements, as listed under measurable goals, are installed and ready for operation the points may be initially claimed and in subsequent years these improvements remain	<pre>(for each pump station upgraded in compliance with this BMP) in the first year the improvements, as listed under measurable</pre>

Kansas Permit No.: M-AR58-SU01 Page 20 of 57

<pre>when main line portional points may be claimed. power fails. > A dialer system, or tolenetry system, or connection to a SCADA system shall be installed to provide real time or nearly real time notification of failures at the pump stalion which can potentially lead to sanitary sewer overflow. > The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven pump stalion state at eat a state at least equal to the firm pump station the pump station for immediate concertives subject of any station shall be sized to pump station this NRP. The pump station this NRP. The pump station this NRP.</pre>		uhan main 11		T
<pre>> A dialer system, or elemetry system, or connection to a SCADA system shall be installed to provide real time or nearly real time potentially lead to senitary sever overflow.</pre> > The pormittee shall purchese and maintain for immediate operation a trailer mounted motor driven pung station falla to operate. The motor driven searitary sever overflow. > The pormittee claims points for under this motor driven pung station falla to operate. The motor driven pung station falla to coperate. The motor driven pung station the firm punging capacity of any sanitary sever pung station the partitee claims points for under this MW. The pung station shall be modified to facilitate the connection of the trailer mounted pung discharge to the force main				
<pre>> A dialer operation, yetem, or d points may be claimed system, or do in the pump station GCADA system operation shall be operation installed to with this time or nearly successive year the notification of improvements, failures at the pump station which can measurable potentially goals, remain lead to sanitary sewer overflow.</pre> > The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven year sewer operation a traile to the sized to pump at a rate at least equal to the firm pump station fails to operate. The motor driven gump station the pimp station fails to operate. The motor driven pump station the firm pump station the pimp station the firm pump station the pimp station the firm pump station the pimp station th		POWET TATTS.	may be claimed.	
<pre>system, or 4 points may be claimed system, or connection to a SGADA system shall be installed to provide real provide real time or nearly real time notification of failures at the potentially lead to which can which can which can potentially lead to some and the potentially shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for uss when the pump station fails to operate. The motor driven pumping capacity of any station shall be modified to facilitate the connection of the pump station the pump station the pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main</pre>				
telemetrybe claimedsystem, or connection to afor (for each pump stationshall be installed towith thisinstalled towith thisprovide realMP! eachtime or nearlyyear the improvements, failures at the potentiallypotentiallygoals, remain operational.overflow.>>The permittee shall purchase and maintain fails to operation fails to operationstationfailer improvements, as listed underyear the improvements, operational.ited to sanitary sewer operation fails to operate. The motor driven pump station fails to operate. The motor driven pump station fails to operate. The motor driven pump station fails to operate. The motor the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP.The pump station the permittee claims points for under this BMP.The pump station of the fram pump pump station the face main	كر			1
<pre>system, or for for each pump station installed to installed to provide real time or nearly real time notification of failures at the pump station which can which can which can potentially lead to operational.</pre>		-		
<pre>connection to a shall be installed to provide real time or nearly real time notification of failures at the pump station which can potentially lead to sanitary sever overflow.</pre> The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The metage to the firm pump station the permittee sized to pump at a rate at least equal to the firm pump station the permittee sized to pump at a rate at least equal to the firm hell be modified to facilitate the connection of the trailer mounted pump discharge to the force main				1 1
SCADA system shall be installed to provide real time or nearly real time notification of failures at the pump station which can potentially lead to sanitary sewer overflow. > The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump station fails to operate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under the pump station the permittee claims points for under mounted gump discharge to the firm monted gump				
<pre>shall be installed to provide real time or nearly real time notification of failures at the pump station which can potentially lead to sanitary sewer overflow.</pre> The permittes shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pump station the parmittee claims points for under this BWP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the form mounted pump discharge to the form mounted pump discharge to the form mounted pump discharge to the form discharge to the form mounted pump discharge to the form mounted pump discharge to the form discharge to the form mounted pump discharge to the form discharge to the fo				
<pre>installed to provide real imported real time or nearly real time outification of failures at the pump station which can potentially lead to sanitary sewer overflow. > The permittee shall purchase and maintain for immediate ouperation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump station the fails to capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station the point te claims points BMP. The pump discharge to the farm mounted the farm farm farm farm farm farm</pre>				upgraded in
provide realBMP) eachtime or nearlyyear thenotification ofimprovements,failures at theas listedpump stationmeasurablewhich canpotentiallylead tosanitary seweroverflow.operational.>The permitteeshall purchaseand maintainfor immediateoperationalmotor drivensewage pump foruse when thepump stationpump stationfails tooperate. Themotor drivenpump stationfails tooperate at least equal tothe firmthe permitteeclaims pointsfor under thisBMP.The pumpstation shallbe modified tofacilite theconnection ofthe trailermounted pumpdischarge to		shall be		compliance
<pre>time or nearly successive real time notification of failures at the pump station which can potentially goals, remain lead to sanitary sewer overflow.</pre> The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pump ing capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the for main set of the trailer mounted pump discharge to the for main set of the trailer mounted pump discharge to the for main set of the trailer mounted pump discharge to the for main set of the trailer mounted pump discharge to the for main set of the trailer mounted pump discharge to the for main set of the for main set of the trailer mounted pump discharge to the for main set of the for main se		installed to		with this
<pre>real time vert the vert t</pre>		provide real		BMP) each
<pre>real time vert the vert t</pre>		time or nearly		successive
notification of failures at the pump station which can solution which can botentially lead to sanitary sewer overflow.improvements, as listed under measurable goals, remain operational.>The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pump station the station shaltary sewer pump station the permittee clains points for under this BMP.The pump station shall be modified to facilitate the connection of the trailer minThe pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the fore main				year the
failures at the pump station which can potentially lead to sanitary sewer overflow.a listed under measurable goals, remain operational.> The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pump station the permittee clains points for under this DWP.The pump station shall be modified to facilitat the connection of the trailer mounted pump discharge to the fore main		notification of		
<pre>pump station which can potentially lead to sanitary sewer overflow.</pre> The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the fore main				
<pre>which can measurable potentially lead to sanitary sewer overflow. > The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pump for use where pump station for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the fore main</pre>				1 1
<pre>potentially lead to sanitary sewer overflow. > The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main</pre>				
<pre>iead to sanitary sewer overflow. > The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main</pre>				
<pre>sanitary sewer overflow. > The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main</pre>				
overflow. > The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station static the connection of the trailer				operacional.
The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		OVELITOM.		
shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main	حر			
for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		_		
operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to				
use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		sewage pump for		
fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		use when the		
operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		pump station		
The pump stall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		fails to		
pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		operate. The		
sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		motor driven		
at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		pump shall be		
at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		sized to pump		
the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		least equal to		
pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		-		
capacity of any sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
sanitary sewer pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
pump station the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
the permittee claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
claims points for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
for under this BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
BMP. The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		-		
The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		PLIE .		
station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main		The nump		
be modified to facilitate the connection of the trailer mounted pump discharge to the force main				
facilitate the connection of the trailer mounted pump discharge to the force main				
connection of the trailer mounted pump discharge to the force main				
the trailer mounted pump discharge to the force main				
mounted pump discharge to the force main				
discharge to the force main				
the force main				
and convenient				
		and convenient	L	

Kansas Permit No.: M-AR58-SU01 Page 21 of 57

	installation of		
	the suction		
	line from the		
	trailer mounted		
	pump into the		
	wet well.		
Lbmp I D D & E - 09			
Provide a contribution	The contributions may	The total value of	
to area recycle	be made to programs	donation (either	
programs or programs	which take tires,	in-kind work,	
(such as household hazardous waste	automotive fluids,	materials, supplies	
disposal facilities,	batteries, or other wastes for which there	or cash) in a minimum amount of	
e-cycle facilities,	is any documentation	\$500 must be made	
paper shred	such wastes have been	in the year points	
facilities,	discarded as addressed	are claimed.	
pharmaceutical	under the BMP summary,		
disposal facilities	The contributions must	Alternatively, for	
etc.) designed to	total a minimum of	municipalities with	
properly dispose of	\$500 in the year (\$100	less than 500	2 points may
types of waste or	in the year for	population the	be claimed
materials which have	alternative lower	total value of	each year
previously been	population	donation in a	this BMP goal
discarded to or	municipalities) which	minimum amount of	is achieved.
adjacent to either the	points are claimed.	\$100 must be made	
MS4, streams, or lakes	The contributions can	in the year points are claimed.	
within or adjacent to the permittee's permit	be monetary or can be in the form of goods	are crarmed.	
area. The area	and/or services with		
program must be within	an agreed specified		
30 miles from this	value. Contributions		
permit area.	may be made to area		
	household hazardous		
	waste programs,		
	private recycle/reuse		
	facilities or civic/volunteer		
	organizations		
	assisting in recycle.		
Lbmp I D D & E - 10			3 points may
			be claimed
	Generate a summary	The inspection	for
Inspect, 5% of the MS4	report of the	process can occur	inspection of 2% of the MS4
system Stormwater inlets and/or outfalls	inspection including the number of inlets	in a single calendar year or	system in the
within the permit area	and/or outfalls	may be conducted	year the
all conducted within a	visually inspected,	over a period	required
12-month period to aid	condition comments,	extending from one	percentage of
in identifying illicit	illicit discharges	year into the	inlets and/or
discharges. If in a	identified and the	succeeding year.	outfalls are
12-month period 15% of	results of efforts to	Points may be	finally
the MS4 system inlets	eliminate illicit	claimed in the year	inspected,
and/or outfalls are	discharges, e.g.,	when the televised	alternately
		1 1 -	1 16 150 . 6
inspected a higher point value may be	discharge line disconnected and	and/or visual inspection of this	if 15% of the MS4 system is

claimed in the year	redirected to the	portion of the MS4	inspected 5
the required	sanitary sewer or	system (either 2%	points may be
percentage of	discharge practice	or 15%) is	claimed.
inspections are	terminated.	completed.	
completed.			

- g. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Illicit Discharge Detection and Elimination requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- h. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

4. Construction Site Stormwater Runoff Control

The permittee shall continue to maintain a program to reduce pollutants in any stormwater runoff to the MS4 from construction activities that result in a land disturbance of greater than or equal to one acre. Reduction of pollutant discharge associated with stormwater from construction activity disturbing less than one acre must be included in the program if that construction activity is part of a larger common plan of development or sale that would disturb one acre or more. The program must include, at a minimum, all the following:

- a. Maintain and enforce an ordinance, a resolution, or other enforceable requirement, if the permittee has the authority to do so, to require erosion and sediment controls, as well as sanctions to ensure compliance, to the extent allowable under State and local law. A copy of the ordinance or resolution shall be submitted to KDHE with the annual report if requested by KDHE.
- b. Maintain requirements for construction site owners or operators to implement appropriate erosion and sediment control best management practices.
- c. Maintain requirements for construction site owners or operators to control waste such as discarded building materials, concrete truck washout, chemicals, litter, and sanitary waste at the construction site that are likely to cause adverse impacts to water quality.
- d. Maintain procedures for site plan review which incorporate consideration of potential water quality impacts.
- e. Maintain procedures for receipt and consideration of information submitted by the public.
- f. Maintain procedures for site inspection and enforcement of control measures.
- g. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 4 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 6 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings; a single public hearing can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Construction Site Stormwater Runoff Control program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp C S S R C - 01			
Implement a requirement for a Soil Erosion and Sediment Control(SESC) Plan for any land Disturbance sites which are either equal to or greater than 1 acre or for which there is construction activity disturbing less than one acre which is part of a larger common plan of development or sale that in total disturbs one acre or more.	Enact a regulatory ordinance, or other enforceable measure that requires an SESC Plan for all developments disturbing sites which are either equal to or greater than 1 acre or for which there is construction activity disturbing less than one acre which is part of a larger common plan of development or sale that in total disturbs one acre or more.	Points may be claimed in the year the ordinance/enforceab le requirement first becomes effective, and for each full calendar year thereafter for which the ordinance/enforceab le requirement remains effective.	3 points may be claimed in the year the ordinance initially becomes effective, and 2 points may be claimed for each successive year thereafter for which the ordinance remains effective.
Lbmp C S S R C - 02	One acre or more.		
Develop and adopt a design manual for erosion and sediment control BMPs which are required to be used on sites which will be disturbed and are either equal to or greater than 1 acre or for which there is construction activity disturbing less than one acre which is part of a larger common plan of development or sale that in total disturbs one acre or more.	Require implementation of BMPs in compliance with the design manual on all sites which meet the disturbed area standard as specified.in the BMP Summary.	Points may be claimed for the year which the manual is initially adopted and implemented, and a reduced number of points may be claimed for subsequent years in which the manual remains implemented.	3 points may be claimed in the year the manual is initially implemented, and 2 points may be claimed for each successive year the manual remains effective.

Kansas Permit No.: M-AR58-SU01 Page 24 of 57

Provide access to at least one training class for contractors, developers or others involved with land disturbance projects which provides training on requirements for a Stormwater Pollution Prevention Plan (SW2 Plan) and implementation of appropriate BMPs.This training class must address the requirements for permits.Points may be claimed for the year in which the training class is held.3Develop a site plan review process which construction as well as post construction impacts.Review process must have written guidance for the reviewer. Issuance of a building start construction may not be provided until the site plan has successfully passed the review process submittal or has been modified to comply with requirements identified during the review process. Measures must be included to enforce the installation of water quality BMPs included in the site plan.Points may be claimed in the year the review process is initially implemented.3 pdDevelop a site plan review process which may occur during (construction impacts.Review process must have written guidance for the review process claimed in the year to approvate to submittal or has been modified to comply with requirements identified during the review process. Measures must be included to enforce the installation of water quality BMPs included in the site plan.Points may be claimed in the year to model in the site plan.Ibmp C S S R C - 053 pd	S R C - 03			
involved with land disturbance projects which provides training on requirements for a Stornwater Pollution Prevention Plan (SWP2 Plan) and implementation of appropriate BMPs.requirements for permits.held.3Lbmp C S S R C - 04permits.Points may be claimed in the year the review process which considers potential which may occur during construction as well as post construction impacts.Review process must have written guidance for the reviewer. Issuance of a building permit or approval to start construction may not be provided until the site plan has successfully passed the review process either based on the initial site plan submittal or has been modified to comply with requirements identified during the review process. Measures must be included to enforce the installation of water quality BMPs included in the site plan.Points may be claimed in the year the review process continues to be implemented.3Develop a site plan review process either based on the initial site plan submittal or has been modified to comply with requirements included to enforce the installation of water quality BMPs included in the site plan.Points may be continues to be implemented.5Lbmp C S S R C - 053po	access to at Thi a training mus c contractors, req	address all local rements for a	claimed for the year in which the	
Develop a site plan review process which considers potential water quality impacts which may occur during construction as well as post construction impacts.Review process must have written guidance for the reviewer. 	with land req imports imported and cements for a req er Pollution per implementation priate BMPs,	rements for mentation of BMPs ddress the rements for		3 points
review process which considers potential water quality impacts which may occur during construction as well as post construction impacts.have written guidance for the reviewer. Issuance of a building permit or approval to start construction may not be provided until the site plan has successfully passed the review process either based on the initial site plan submittal or has been modified to comply with requirements identified during the review process. Measures must be included to enforce the installation of 	S R C - 04			
Lbmp C S S R C - 05	rocess which have s potential for ality impacts Iss y occur during per tion as well as sta struction not the eit ini sub mod wit ide rev Mea inc the wat inc	written guidance he reviewer. nce of a building t or approval to construction may be provided until ite plan has ssfully passed review process or based on the al site plan ttal or has been fied to comply requirements ified during the w process. Thes must be aded to enforce installation of c quality BMPs aded in the site	claimed in the year the review process is initially developed and implemented. Also points may be claimed in each subsequent year the review process continues to be	3 points may be claimed in the year the review process is initially developed and implemented, 2 points may be claimed for each successive year the review process continues to be implemented.
Establish effective requirements for construction sites to Develop through enforceable means requirements for construction siteEnact ordinance or of ther effective means to achieve control of wastes at construction sites.Points may be claimed in the year points may be points may be points may be be claimed in each subsequent year the method of effective year construction site of poerators or owners to control wastes. At aEnact ordinance or ordinance or sitesPoints may be claimed in the year of enactment. Also points may be points may be claimed in each subsequent year the succontrol of method of effective waste remains in effect.	SRC-05 h effective Ena ents for oth tion sites to to wastes. was through sit e or other ole means ents for tion site s or owners to wastes. At a	ordinance or effective means hieve control of as at construction	claimed in the year of enactment. Also points may be claimed in each subsequent year the method of effective control of construction site waste remains in	3 points may be claimed in the year of enactment, 2 points may be claimed for each successive year the method of effective control of construction site waste

Kansas Permit No.: M-AR58-SU01 Page 25 of 57

,

The procedures document must address the administrative aspects associated with required inspections of construction sites, the issuance of	Development of the written procedures and the Inspection Guide can occur in any year. Initial	
inspection reports, notices of violations, and enforcement actions. The Inspection Guide must provide inspectors guidance on how to conduct a construction site stormwater inspection, the required procedures, and guidance on acceptable conditions of various BMPs employed on such sites, enforcement actions and/or reference of cases for enforcement by other municipal staff, guidance on photo log of the inspection and inspection.	<pre>implementation can allow points to be claimed in that year and continued implementation can allow points to be claimed in subsequent years.</pre>	3 points may be claimed in the year of initial development, 2 points may be claimed for each successive year the written procedures and inspection guide continue to be utilized.
The tracking system must allow for scheduling inspections and follow-up activities such as re- inspections, mailing notices or reports, etc.	A point can be claimed in the initial year the software tracking system is implemented and each year thereafter it is	<pre>1 point may be claimed for any year the software is initially utilized, and 1 point may be claimed for each successive</pre>
acer errer errer guo ciu f ciu f ciu s a a a a a a a a a a a a a a a a a a	cceptable conditions f various BMPs mployed on such ites, enforcement ctions and/or efference of cases for nforcement by other unicipal staff, uidance on photo log f the inspection and hspection checklists or use by the hspector. he tracking system ust allow for cheduling inspections nd follow-up ctivities such as re- nspections, mailing otices or reports,	cceptable conditions f various BMPs mployed on such ites, enforcement ctions and/or eference of cases for nforcement by other unicipal staff, uidance on photo log f the inspection and nspection checklists or use by the nspector. A point can be claimed in the initial year the software tracking system is implemented and each year

- h. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Construction Site Stormwater Runoff Control requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- i. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.
- 5. Post-Construction Stormwater Management in New Development and Redevelopment Projects

The permittee shall continue to maintain a program to address post-construction stormwater runoff from new development and redevelopment projects that disturb greater than or equal to one acre, including projects less than one acre that are part of a larger common plan of development or sale, that discharge into the MS4. The program must include, at a minimum, all the following:

- a. Maintain a requirement for BMPs to prevent or minimize adverse water quality impacts.
- b. Maintain strategies which include a combination of structural and/or nonstructural BMPs appropriate for the municipality.
- c. Maintain and enforce an ordinance or resolution, if the permittee has the authority to do so, to address post-construction runoff from new development and redevelopment projects to the extent allowable under State and local law.
- d. Ensure adequate long-term operation and maintenance of structural BMPs.
- e. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 5 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 7 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings; a single public hearing can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Post-Construction Stormwater Management in New Development and Redevelopment Projects program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

Kansas Permit No.: M-AR58-SU01 Page 27 of 57

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp P-C S M - 01			
Derelen and edept a		Development of the	
Develop and adopt a custom design manual	The custom design manual shall impose	Development of the design manual can	
for Post-Construction	requirements to	occur in any year.	4 points may
Stormwater Management	achieve at least one	Initial	be claimed in
which specifies	of the following	implementation can	the year of
various structural	standards:	allow points to be	initial
BMPs which are		claimed in that	implementation
required for new	> Capture, at	year and continued	of a custom
development and re- development	least, the first 0.5 inches of	implementation can allow points to be	design manual - alternately
construction sites	precipitation on	claimed in	6 points may
which are greater than	the	subsequent years.	be claimed in
1 acre or for which	development/re-	÷. ÷.	the year of
there is construction	development site		initial
activity disturbing	and utilize		implementation
less than one acre	methods to		of the APWA
which is part of a	prevent		5600
larger common plan of development or sale	discharge off- site, including		stormwater design
that in total disturbs	but not limited		criteria and
one acre or more.	to:		the MARC/APWA
	• retain on-		BMP Manual,
Alternately, adopt and	site		3 points may
implement the APWA	• infiltrate		be claimed for
5600 Stormwater Design	• evaporate		each .
Criteria and the MARC/APWA BMP Manual.	 transpire or 		successive
Third fill Milling Handar.	beneficial		year compliance
	ly reuse		with the
			custom design
	> Through		manual is
	implementation		required/imple
	of appropriate		-mented
	BMP(s) reduce		Alternately 5
	the peak stormwater flow		points may be claimed in
	rate to a value		each
	equal to or less		successive
	than the rate		year the
	which would be		implementation
	experienced on		of the APWA
	the site prior to the		5600 stormwater
	development/re-		design
	development		criteria and
	project based		the MARC/APWA
	upon modeling a		BMP Manual is
	standard storm		required/imple
	event, e.g. 1.0		-mented.
	inch - 6-hour		
	event assuming		
	saturated soil conditions.		
	CONDICIONS.		

Kansas Permit No.: M-AR58-SU01 Page 28 of 57

Ibmp P-C S M - 02	 Other sizing or detention standards generally accepted by design engineers as adequate for the permittee's local. As an alternative to a custom design manual the APWA 5600 Stormwater Design Criteria and the MARC/APWA BMP Manual may be adopted and implemented. Measures must be included to enforce the installation of the various structural BMPs required. 		
Develop a list of post-construction structural or non- structural BMPs which are required to be incorporated in any development/re- development project. The list must include guidance regarding the BMPs which must be incorporated in various projects as determined appropriate by the permittee. The list is to be provided to entities involved with the design of projects prior to site plan review by the permittee.	Development and implementation of the list and guidance is necessary to claim points in the first year. The list of required BMPs must be enforceable through ordinance or other means.	Development of the list and guidance can occur in any year. Initial implementation can allow points to be claimed in that year and continued implementation can allow points to be claimed in subsequent years.	3 points may be claimed in the year of initial implementation , 2 points may be claimed for each successive year the list is maintained and implemented.
Lbmp P-C S M - 03 Develop and implement a program to ensure adequate	The program shall be detailed in a written document and made	Development of the program can occur in any year.	3 points may be claimed in the year of initial implementation

Kansas Permit No.: M-AR58-SU01 Page 29 of 57

long-term cleaning,	available to all	Initial	2 points may
operation and maintenance of all	pertinent maintenance staff.	implementation can allow points to be	be claimed for each
municipally owned or	Stall.	claimed in that	successive
operated post- construction		year and continued implementation can	year the program is
structural stormwater		allow points to be	maintained and
BMP facilities. The program shall address		claimed in subsequent years.	utilized.
several different types of these BMP			
systems. The systems,			
which are addressed, shall include any type			
of post-construction			
structural BMP system, contained in the MS4.			
These shall include, if so present, at a			
minimum the following:			
 detention ponds retention ponds 			
> grass swales			
pervious paving systems			
wetlandsvegetative			
filter strips			
<pre>manufactured stormwater</pre>			
treatment			
devices (swirl separators,			
<pre>screens, etc.) > drop inlet-catch</pre>			
basin			
Lbmp P-C S M - 04			
Develop a master plan	Runoff problems can be	After <u>all</u> aspects are implemented	5 points may
or comprehensive development plan which	addressed efficiently with sound planning	including final	5 points may be claimed in
establishes zoning and	procedures. This	implementation of	the year all
development standards	master or	the master or	aspects are
with establishment of both structural and	comprehensive development plan must	comprehensive development plan,	initially implemented,
non-structural BMPs	include, if not	along with	2 points may
intended to avoid or	already implemented, a	enactment of the	be claimed for
minimize adverse water	zoning ordinance, a	required	each
quality impacts post-	stream buffer	ordinances points	successive
construction.	ordinance, site plan development	for implementation of this BMP can	year all aspects
	requirements which	initially be	continue to be
	include minimizing the	claimed.	implemented.
	increase of impervious		
	surfaces and		
	<pre>maximization/preservat ion of open space.</pre>		
	1 ton of oben shace.	1	1

	The plan must also impose requirements for new development or re-development projects to utilize stormwater retention or detention BMPs and vegetative BMPs (such as grassy swales, filter strips, artificial wetlands, and rain gardens).		
Lbmp P-C S M - 05			
Develop and implement a program for inspection of permittee owned structural BMPs which	The program shall require inspection of at least 10% of the structural BMPs on an annual basis.	The program shall be developed and implemented within a single year.	
includes implementation of needed maintenance to ensure long-term operation of the BMPs	<pre>Identified maintenance activities shall be completed: 1. in the same year of inspection or 2. completed as dictated by the permittee's maintenance/O&M plan 3. or a written plan for completion of the necessary maintenance shall be completed in the same year of inspection with the objective for completion of the maintenance activity within 18 months.</pre>		3 points may be claimed in the year the program is initially developed and implemented, 2 points may be claimed for each successive year the program continues to be implemented.
Lbmp P-C S M - 06 Develop and implement a program for inspection of known privately owned structural BMPs which includes providing the	The program shall require inspection of at least 10% of the known privately owned structural BMPs on an annual basis.	The program shall be developed and implemented within a single year.	3 points may be claimed in the year the program is initially developed and implemented, 2 points may be claimed for

Kansas Permit No.: M-AR58-SU01 Page 31 of 57

owner of the BMPs an inspection report which specifies needed maintenance to ensure long-term operation of the BMPs.	Identified maintenance activities shall be completed in the same year of inspection or a written plan for completion of the necessary maintenance shall be completed in the same year of inspection with the objective for completion of the maintenance activity within 18 months.		each successive year the program continues to be implemented.
Lbmp P-C S M - 07 Enact either an ordinance, a resolution, or other enforceable requirement which requires the installation of pervious surfaces on property.	The ordinance or resolution or other enforceable requirement must specify when installation of impervious surfaces is not acceptable and what allowable pervious surfaces can be installed in lieu of impervious surfaces.	The year the ordinance or resolution or other enforceable requirement is implemented points may be claimed and continued implementation can allow points to be claimed in subsequent years.	3 points may be claimed in the year of initial implementation ' 2 points may be claimed for each successive year the ordinance or resolution or other enforceable requirement is implemented.
Lbmp P-C S M - 08 Implement a program to encourage residential owners to install stormwater BMPs, including but not limited to, native trees, native flower gardens, rain gardens, rain barrels, pervious surfaces, and vegetated swales.	A program which results in installation of such BMPs on 1% of the residential parcels in a year will allow two points to be claimed for that year. In a year when installation of such BMPs on 5% of the residential parcels occurs, a larger number of points may be claimed.	The number of residential parcels improved to qualify for points must occur in a single calendar year.	<pre>2 points may be claimed in a year BMPs are installed on 1% of the residential parcels, 4 points may be claimed in a year BMPs are installed on 5% of the residential parcels.</pre>

Kansas Permit No.: M-AR58-SU01 Page 32 of 57

- f. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Post-Construction Stormwater management in New Development and Redevelopment Projects requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- g. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

6. Pollution Prevention/Good Housekeeping for Municipal Operations

The permittee shall continue to implement an operation and maintenance program that includes employee training to prevent and reduce stormwater pollution from municipal operations activities such as park and open space maintenance, fleet and building maintenance, new construction and land disturbances, and stormwater system maintenance.

a. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 4 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 6 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings; a single public hearing can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Pollution Prevention/Good Housekeeping for Municipal Operations program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp P P/G H - 01			3 points may be claimed in the year the
Install a screening device or method at a single municipal storm sewer outfall or on the storm sewer line immediately upstream of the outfall to reduce the discharge of floatables or other	The screening device or method is required to remove objects that exceed at least 1½ inches in size. The device or method must be capable of continuous operation	Volume or weight of the material shall be documented for either each discharge event or on a quarterly basis.	screening device or method is initially implemented, 2 points may be claimed for each successive

Kansas Permit No.: M-AR58-SU01 Page 33 of 57

year the screening device or method ntinues to be plemented.
levice or method ntinues to be
ntinues to be
be
plemented.
points may
claimed in
the year recycle
tainers are
e available
r municipal aff use and
ne recycle
rogram is
initially plemented,
points may
claimed for each
uccessive
year the
recycle
program ontinues to
be
plemented.
points may claimed in
ne year the
guidance ocument is
nalized and
plemented,
oint may be laimed for
each
uccessive
year the
guidance document
ontinues to
be
nplemented.

Kansas Permit No.: M-AR58-SU01 Page 34 of 57

required by that			
Department.			
Lbmp P P/G H - 04			
Implement a program, with guidance to municipal staff or third-party contractors, to ensure any municipal vehicle or other mechanical equipment washing is conducted in a manner which ensures the wash water is disposed of in the sanitary sewer or otherwise receives proper treatment prior to discharge to the environment.	Maintain proper wash facilities for municipal staff to wash vehicles and/or equipment or implement a program which includes guidance to municipal staff to take vehicles and/or equipment to commercial wash facilities, either of which ensures the wash water is conveyed to the sanitary sewer, or otherwise receives proper treatment prior to discharge to the environment, and not discharged untreated to the MS4 or directly to the environment.	The guidance document must be finalized and implemented in the year which points are initially claimed.	2 points may be claimed in the year the guidance document is finalized and implemented, 1 point may be claimed for each successive year the guidance document continues to be implemented.
Lbmp P P/G H - 05 Implement a program for street sweeping in which the street sweepings are collected and disposed of properly or recycled/reused if possible.	All paved streets which can be swept shall be listed in the schedule for street sweeping. A log shall be maintained listing the street segments which are swept and, dates of sweeping and where the street sweepings are disposed or where the material was sent to be recycled and/or reused. Alternatively, for municipalities with less than 500	At least 10% of the streets which are listed in the street sweeping schedule must be swept at least once in a year to claim points for the year. In years when street sweeping equipment is purchased for use by the permittee additional points may be claimed. Alternately, for municipalities with less than 500	3 points may be claimed in the year at least 10% of the listed streets are swept and street sweeping equipment is purchased, 2 points may be claimed for each year at least 10% of the listed streets are swept or alternately for municipalities
	population street sweeping can be limited to sweeping the gutters. The log which must be maintained need only indicate the street segments which were	population at least 5% of the street gutters which can be swept must be swept in a year to claim points for the year.	with less than 500 population if at least 5% of the street gutters which can be swept are swept in a year 2 points

Lbmp P P/G H - 06	swept in the year and confirm the sweepings were properly disposed or recycled and/or reused		may be claimed.
Develop an employee training program to ensure permittee's staff understand what actions they can take in the workplace to minimize stormwater pollution.	Provide guidance documents in the form of either fact sheets, flyers or e-mails to staff to coach them in appropriate actions they can take while working to minimize stormwater pollution. Alternately, provide in-person training or videos with sign-in- sheets for signature documentation of personal or video training. Retain copies of the guidance documents and/or sign-in-sheets. A log of when the guidance was distributed, or training was provided to staff should be maintained. Provide appropriate guidance and/or training to staff a minimum of twice per year.	For each year in which staff receive guidance documents or in-person training or video training on two separate dates, points may be claimed for the year.	In years when guidance documents or training (in- person or video) are provided on two separate dates 1 point may be claimed.
Lbmp P P/G H - 07 Implement a program to inspect stormwater inlets to identify illicit discharges and clean drop inlets of accumulated debris.	Inspect at least 5% of all inlets annually. Additionally, if 10% of all inlets are inspected in a year an additional point may be claimed. For any inlets which have evidence of dumped paint, oil or other substances which are considered illicit discharges follow up with efforts to educate individuals near the impacted	For each year in which staff inspect at least 5% of all stormwater inlets at least one point may be claimed.	In years when staff inspect at least 5% of all stormwater inlets and remove accumulated debris 1 point may be claimed. In years when staff inspect at least 10% of all stormwater inlets and remove accumulated debris 2 points may be claimed.

Kansas Permit No.: M-AR58-SU01 Page 36 of 57

Lbmp P P/G H - 08	<pre>inlet about illicit discharges. For inlets which have any accumulation of debris, remove the debris for proper disposal.</pre>		
Develop, implement and keep updated an online storm sewer map accessible to the public.	Map shall cover the entire MS4 within the permit area and include all the MS4 lines both pipe and open drainage (i.e. ditches) and shall also illustrate all impaired waterways (i.e. 303(d) listed and TMDL listed streams/rivers) with an indication of the listed impairment.	For each year in which the map is posted online points may be claimed. In the first year the map is posted it must be posted for at least six months for points to be claimed.	3 points may be claimed in the first year, 2 points may be claimed for each year thereafter for which the map remains posted.
Lbmp P P/G H - 09 Identify permittee owned facilities, open space and buildings that can be retrofitted for stormwater BMPs.	Retrofit projects can include: green infrastructure, catchment improvements, Pollutant of Concern targeted BMPs, and native plant restoration projects.	The site(s) must be retrofitted with stormwater BMPs as listed in the measurable goals. Points can be awarded in the first year the BMPs are installed and begin operation and points may be claimed for each year the retrofitted BMPs continue to be operated.	<pre>1 point may be claimed in the first year for each site retrofitted (up to two sites/points maximum, 2 points may be claimed for each year at least two sites continue to operate all of the retrofitted BMPs which were installed.</pre>
Lbmp P P/G H - 10 Install and operate a constructed wetland at a municipal facility such as at a parking lot, shop, maintenance facility, rest area or any other industrial/commercial type facility, e.g. recycling facility,	The wetland shall include a water surface area of at least 1/4 acre or equivalent submerged surface area for submerged wetlands.	Points may be claimed in the year the wetland is constructed and in subsequent years the wetland remains in operation.	2 points may be claimed for the year in which the wetland is constructed, 1 point may be claimed for each subsequent year the wetland

Kansas Permit No.: M-AR58-SU01 Page 37 of 57

<pre>Index of this permit area. The canopy or other covered area for load- out of salt or other de-loing materials may be installed at a facility owned by the permittee or at a facility is located within 30 miles of this permit area. Ibmp P F/G H - 12 Install a stormwater treatment system for capture of either trash. sediment, or debris. Systems may include any proprietary stormwater treatment system included no svorf similar custom similar custom storm sewer line installed at a single included no svorf storm sewer line intigial storm sewer outfall or on the storm sewer line immediately upstream of the outfall to reduce the discharge</pre> Contaminated runorr mates of this permit area is constructed, 2 points may be claimed for each subsequent year the canopy/covered area remains in operation. Volume or weight of the material shall be documented for either each discharge event, on a quarterly basis or at least annually. implemented, or weight) captured and prevented from designed systems. A system can be inmediately upstream of the outfall to reduce the discharge Contaminated runorr designed by the implemented, or weight) captured and prevented from discharge to the contaminated runorr overfile material for the outfall to reduce the discharge Contaminated runorr designed by the implemented. Contex to the material shall be documented for elther each discharge to the continues to proprive the discharge or weight) captured and prevented from the system is contex to be implemented. Contex to the the discharge to the Contex to the material for system contex the discharge or weight) captured and prevented from the discharge to the Contex to the discharge to the Conte	transfer station,			remains in
 Install.a.campy or or covered installs.a.campy or covered installed in the composition of solutor installed at a store solution in the solution of solutor of solut	kennel, or airport.			operation.
 other covered area for carea shall be large construction and in the ended of spilled de-icing construction and in subsequent years the canopy/covered area for load-out and channed to precipitation and resulting in containted runoff from the site, during and immediately following load out of sall or other covered area for load-out of sall or other contracts with as long as the facility used by the permittee contracts with as long as the facility is located within 30 miles of this permit reatment system for capture of either trast. Systems may include any proprietary stormwater traster system is overloaded or falls to operate properly at any time. Install a storm sever line storm sever outfall or on the storm sever line toutfall to reduce the discharge to the implemented. 	Lbmp P P/G H - 11			
out of salt or other de-icing materials may be installed at a facility owned by the permittee or at a facility owned by an entity the permittee contracts with as long as the facility is located within 30 miles of this permit area.Subsequent year the canopy/covered area remains in operation.Install a stormwater treatment system treatment systems include any proprietary stormwater including CDS, Hancor, Enviro 21, etc. or similar custom included to system can be installed at a single municipal storm sewer outfall or on the storm sewer line immediately upstream of the outfall to reduce the discharge to the discharge to the discharge to the discharge to the discharge to the discharge to theVolume or weight of the material shall be documented for either each at least annually.3 points may be claimed in the year the treatment system is overloaded or fails to operate properly at any time. A log of the material (noting either volume or weight) captured and prevented from discharge to theVolume or weight of the material succassive a quarterly basis or at least annually.3 points may be claimed in the year the treatment system is overloaded or fails to operate properly at any time. A log of the material (noting either volume or weight) captured and prevented from discharge to theVolume or weight of the material the atterial the atterial successive year the treatment system	other covered area for load-out of salt or other de-icing chemicals where such de-icing materials are stored either within the permit area or a storage facility located within 30 miles of this permit area. The canopy or other	area shall be large enough to allow normal load-out and cleanup of spilled de-icing materials, without mixing with precipitation and resulting in contaminated runoff from the site, during and immediately following load out	claimed in the initial year of construction and in subsequent years the canopy/covered area remains in	be claimed for the year in which the canopy/covered area is constructed, 2 points may be claimed for each
permittee or at a facility owned by an entity the permittee contracts with as long as the facility is located within 30 miles of this permit area.The treatment system or method must be capable of continuous operation during stormwater treatment system include any proprietary stormwater treatment system include to avoid system can be installed at a single municipal storm sewer line immediately upstream of the outfall to reduce the dischargeThe treatment system or method must be capable of continuous operation during stormwater discharges.Volume or weight of the material shall be documented for either each discharge to void surcharging/flooding in the event the system is overloaded or fails to operate properly at any time.Joperation.Manuel Del Del Del Del Del Del Del Del Del D	out of salt or other de-icing materials may be installed at a			year the canopy/covered
as the facility is located within 30 miles of this permit area.and the second	permittee or at a facility owned by an			in operation.
Install a stormwater treatment system for capture of either trash, sediment, or debris. Systems may include any proprietary stormwater treatment system including CDS, Hancor, Enviro 21, etc. or similar custom designed systems. A system can be installed at a single municipal storm sewer outfall or on the storm sewer line immediately upstream of the outfall to reduce the dischargeThe treatment system or method must be capable of continuous operation during stormwater discharges. An emergency bypass or overflow line can be in the event the designed systems. A system can be installed at a single municipal storm sewerThe treatment system other work of the outfall to or weight) captured or weight) captured or weight) captured of the outfall to reduce the dischargeThe treatment system or method must be capable of continuous be continues to the material discharge to theVolume or weight of the material shall be documented for a quarterly basis or at least annually.3 points may the water discharge treatment system is initially implemented, 2 points may be claimed for each successive year the treatment or weight) captured or weight) captured or weight) captured the discharge to theVolume or weight of the material be discharge to theInstalled at a single immediately upstream of the outfall to reduce the dischargeThe treatment is system can be or weight) captured or weight) captured or weight) captured or weight) captured or weight och theVolume or weight of the material till or on the system can be or weight) captured or weight och the the material the material the material the material the materi	as the facility is located within 30 miles of this permit			
of floatables or other receiving water shall objects to receiving be maintained.	Install a stormwater treatment system for capture of either trash, sediment, or debris. Systems may include any proprietary stormwater treatment system including CDS, Hancor, Enviro 21, etc. or similar custom designed systems. A system can be installed at a single municipal storm sewer outfall or on the storm sewer line immediately upstream of the outfall to reduce the discharge of floatables or other	or method must be capable of continuous operation during stormwater discharges. An emergency bypass or overflow line can be included to avoid surcharging/flooding in the event the system is overloaded or fails to operate properly at any time. A log of the material (noting either volume or weight) captured and prevented from discharge to the receiving water shall	the material shall be documented for either each discharge event, on a quarterly basis or	be claimed in the year the treatment system is initially implemented, 2 points may be claimed for each successive year the treatment system continues to be

installed on a		
stormwater line to		
provide treatment at		
problem locations.		

- b. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Pollution Prevention/Good Housekeeping for Municipal Operations requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- c. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

Guidance useful in implementing the six minimum control measures can be obtained from the Online Water Library (OWL) of the Center for Watershed Protection. A list of url links to helpful guidance documents, including OWL, can be found on the KDHE Municipal Stormwater Program website at the following url:

http://www.kdheks.gov/muni/download/MS4 NPDES Permit helpful guidance.pdf

Document titled "MS4 NPDES Permit Helpful Guidance and/or Resources"

D. Total Maximum Daily Load (TMDL) Regulated Pollutants

The Permittee shall continue to review, update, implement and develop, when necessary, structural and non-structural BMPs which will reduce to the Maximum Extent Practicable the discharge of the TMDL regulated pollutants from the MS4 as listed in PART II.

The effort to reduce the discharge of TMDL regulated pollutants is anticipated to be an iterative process with changes in the SMP periodically, generally not more frequently than annually, possibly every two or three years. This "adaptive management" type process is recommended to attenuate the discharge of TMDL regulated pollutants listed in the TMDL Table of PART II of this permit. Each updated SMP document shall provide:

1. Best Management Practices (BMPs)

Updates of the SMP document can include structural and/or non-structural BMPs implemented to reduce the discharge of TMDL regulated pollutants from the MS4. This section of the SMP shall identify or include:

a. BMPs which will be implemented, including non-structural and/or structural measures, as selected from EPA's "National Menu of Best Management Practices (BMPs) for Stormwater" or from a local or regionally appropriate storm drainage criteria manual such as the Kansas City Metro Chapter of the American Public Works Association (APWA) Manual of Best Management Practices for Stormwater Quality or such other BMP manuals as are appropriate (links for the National Menu of Best Management Practices (BMPs) for Stormwater and the Kansas City Metro Chapter of the American Public Works Association (APWA) Manual of Best Management Practices (BMPs) for Stormwater and the Kansas City Metro Chapter of the American Public Works Association (APWA) Manual of Best Management Practices for Stormwater Quality can be found on the KDHE document titled "MS4 NPDES Permit Helpful Guidance and/or Resources" at the following url:

http://www.kdheks.gov/muni/download/MS4 NPDES Permit helpful guidance.pdf

- b. Include a description of non-structural practices being implemented, including the six minimum control measures and/or other source control measures.
- c. Include the location of the structural BMPs.
- d. Identify the design factors associated with the structural BMPs.
- e. Include information on the reported effectiveness of the chosen BMPs based on regionally appropriate data or performance analyses in the International Stormwater BMP Database (a link to the Database can be found on the KDHE document titled "MS4 NPDES Permit Helpful Guidance and/or Resources" at the following url:

http://www.kdheks.gov/muni/download/MS4 NPDES Permit helpful guidance.pdf

- f. Include a schedule for constructing and/or implementing additional selected BMPs to reduce the discharge of TMDL regulated pollutants.
- g. Include an inspection/maintenance plan and schedule for each BMP, as appropriate.
- h. Include a plan and schedule to monitor the effectiveness of the BMPs to reduce the discharge of TMDL regulated pollutants
- 2. Measurable goals to assess the effectiveness of the TMDL BMPs

Overall TMDL measurable goals should be based upon in stream sampling of the stream(s) existing in, or adjacent to the Permit Area (or Permit Areas for cooperative stormwater control efforts as provided in paragraph 4 below) during or immediately following storm events. Alternately, the TMDL measurable goals may be based on stormwater sampling within the MS4 comparing results upstream of the BMP and downstream of the BMP. The monitoring results of samples obtained to determine performance of BMPs should be maintained on file in compliance with the Standard Conditions records retention requirement, these results do not need to be reported to KDHE via the electronic DMR process at this time. However, these monitoring results are to be reported or summarized in the Annual Report as required in PART V REPORTING.

Individual or sub-basin BMP performance goals may include in stream or BMP discharge sampling locations based upon individual BMPs, sub-basin BMPs or aggregate BMPs. Alternatively, the permittee may use modeling that has been properly calibrated to determine that BMP measurable goals are being met.

Measurable goals for reducing TMDL pollutants contributed by MS4s can be expressed in quantifiable values to:

- I. reduce the total mass of pollutants, and
- II. be expressed as average and median values (percent reduction of inflow volume, reduction in pollutant mass loading) or for bacteria as a geometric mean.
- 3. Maps shall be developed and maintained which illustrate:
 - I. The Permit Area, boundaries of the contributing drainage basins and primary sub-basins, within and outside the Permit Area
 - II. The locations of the BMPs, if structural
 - III. The location of TMDL stream monitoring locations, if such monitoring is required
 - IV. Storm sewer collection system which includes the outfalls within the Permit Area where the MS4 drains to TMDL listed impaired streams or lakes
- 4. Alternative Stormwater Offsite Pollution Reduction Program

As appropriate, when waters of the state are affected by TMDL regulated pollutants from both the Permit Area and surrounding non-jurisdictional lands, the permittees may incorporate and implement plans through their SMP for an offsite pollution reduction program to install Best Management Practices (BMPs) in alternative locations, including outside the Permit Area, within the watershed shared by urban entities or urban and non-urban entities. Any alternative stormwater offsite pollution reduction program should be developed with watershed interests, such as other communities, Watershed Restoration and Protection Strategy (WRAPS) groups and Conservation Districts lying outside the Permit Area for the joint purpose of reducing pollutant loads generated from urban and non-urban lands within the shared watershed. Candidate offsite locations and practices will be consistent with implementing existing watershed plans that identify specific urban and non-urban (such as agricultural) BMP types and locations to achieve TMDLs reductions. The Alternative Stormwater Offsite Pollution Reduction Program shall be subject to KDHE approval and approved by KDHE prior to incorporation into the permittee's SMP.

E. The parties responsible for compliance with the SMP document.

F. Monitoring Requirements

Possibly required in PART II.

G. Reporting Requirements

See PART V.

H. Modifications to BMPs and the Stormwater Management Program document

For minor BMP modifications/replacement: Within 60 days of a determination by the permittee or date of written notification from KDHE, the permittee shall modify the BMP if modifications are needed to maintain a program in compliance with this permit.

For major BMP modifications/replacement: These major modifications are defined as ones which normally take more than 60 days to construct and/or implement. Within 60 days of a determination by the permittee or date of notification from KDHE, the permittee shall provide a plan and schedule for the upgrade/replacement of the BMP. The plan and schedule are subject to KDHE approval.

The SMP shall be evaluated annually and, if revisions are necessary, the modified SMP document shall be submitted with the annual report due to KDHE by February 28 of each year.

PART II. TOTAL MAXIMUM DAILY LOAD (TMDL) BEST MANAGEMENT PRACTICES AND SURFACE WATER MONITORING

Permittees who are required to complete storm event monitoring of surface waters, i.e., streams or rivers, (see TMDL Table and associated text) shall report the results of the storm event monitoring with the eDMR reporting system.

A. TMDL BMP IMPLEMENTATION REQUIREMENTS

The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 4 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 6 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timingperiod or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings; a single public hearing can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a TMDL Pollutant Reduction and Monitoring program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp T M D L - 01 Install pet waste stations which include a glove/bag dispenser with signage and waste can to encourage pet waste disposal at either parks, trails,	At least one pet waste station shall be installed at the selected park, trail, rest area or other public land. The station(s) shall	In the year the Measurable Goal requirement is implemented the point may be claimed and for each year	1 point may be claimed for the year in which the Measurable Goal requirements are enacted, and

Kansas Permit No.: M-AR58-SU01 Page 42 of 57

rest areas or other	include signage which	thereafter the pet	1 points may
public lands owned by the permittee.	encourages proper pet waste disposal/cleanup and a waste can.	waste stations remain in use.	be claimed for each subsequent year the Measurable Goal
			requirements remain in effect.
Lbmp T M D L - 02	ner med den som for den forste den en de ged og den kondet forget for de en men ble av gedene	anna (agus é sa destanción éstabliquest concernantes en establicador de la concernante en establicador en esta	3 points may be claimed for the year in
Establish a program to encourage installation of residential rain gardens.	Provide public education on rain gardens and design guidance for the installation of residential rain gardens. The rain gardens must have a minimum area of 20 square feet. The installation of rain gardens on five various residential parcels shall qualify the permittee to claim points for this BMP.	In the year five or more residential rain gardens are finally constructed and become operational the points may be initially claimed and in subsequent years when at least five residential rain gardens remain operational points may be claimed.	<pre>which five or more residential parcels install rain gardens and initiate operation, 2 points may be claimed for each subsequent year at least five or more residential parcels have rain gardens remain in operation.</pre>
Lbmp T M D L - 03			3 points may be claimed for
Install and operate a constructed wetland.	The wetland shall include a water	Points may be claimed in the year	the year in which the wetland is
	surface area of at least one acre or equivalent submerged surface area for	the wetland is constructed and in subsequent years the wetland remains	constructed, 2 points may be claimed for each
	submerged wetlands.	in operation.	subsequent year the
			wetland remains in operation.
Lbmp T M D L - 04	nan in sole distance di se putto interne por da bili.	namu, e smul - 19 Fordard (1913)	3 points may be claimed for
Enact a stream buffer ordinance, resolution, or other enforceable requirement to impose stream buffer standards.	The enactment of stream buffer standards must include enforcement capability. Consider use of the EPA stream buffer model ordinance or similar such requirement.	The year the ordinance, resolution or other enforceable requirement is enacted points may be claimed. Also points may be claimed for	the year in which the ordinance, resolution or other enforceable requirement is enacted, 2 points may be claimed for

Kansas Permit No.: M-AR58-SU01 Page 43 of 57

		subsequent years the ordinance, resolution or other enforceable requirement remains in effect.	each subsequent year it remains in effect.
Lbmp T M D L - 05			
Develop a pet waste brochure or flyer document to educate the public about animal waste contamination of stormwater. The document encourages pet owners to pick up their pet's waste. Alternately, post the document on social media or the municipal website.	The brochures or flyers are to be posted in various public buildings and distributed to the public throughout the year. In the year the number of documents shall equal or exceed the most recent U.S. Census Bureau decennial housing units value for the permit area. The applicable U.S. Census housing units value shall be documented, and the number of documents distributed shall also be documented. This information and copies of the documents shall be retained on file.	The documents may be distributed in any fashion and at any time throughout the year. Documents posted on website(s) shall be posted for at least six months in the year. Documents posted on social media shall be posted six times within the year points are claimed.	<pre>1 point may be claimed in a year in which the required number of brochures and/or flyers are distributed, documents posted on social media or the website must be posted for at least as specified.</pre>
	website shall have the page copied and printed to retain on		
	file.		
Lbmp T M D L - 06			
Distribute "Only Rain Down the Drain" door hangers or similar document.	Provide in portions of the permit area with suspected illicit discharges. In the year the number of documents distributed shall equal or exceed	The documents may be distributed in any fashion and at any time throughout the year. Alternately, the	2 points may be claimed in a year in which the required number of hangers or similar documents are distributed or
	10% of the most recent U.S. Census Bureau decennial housing units value for the permit area. The applicable U.S. Census housing units value shall be documented, and the number of	document may be posted to social media (at least three times in the year) or posted on the municipal website for a minimum of three months in the year	alternately posted to social media or the municipal website for the required time.

	documents distributed shall also be documented. This information and copies of the documents shall be retained on file.	to qualify for points	
Lbmp T M D L - 07 Inspect 10% of all known MS4 outfalls for dry weather discharges either annually or twice per year to identify potential illicit discharges.	Complete inspection of all known MS4 outfalls either annually or twice per year during dry weather periods. If dry weather discharge is found follow-up with investigation to determine if a portion or all the discharge is illicit. Document the findings and initiate efforts to eliminate any identified illicit discharges.	The inspections must be conducted either annually or if twice per year they must be seasonal within the same calendar year (winter, spring, summer, and fall). Points can be claimed for that year. In addition, if an illicit discharge is detected and eliminated in association with this inspection program additional points may be claimed in the year detected or in the year the discharge is eliminated.	3 points may be claimed for annual inspection as required by this BMP, 5 points may be claimed for these inspections completed twice in a year, and if an illicit discharge is detected <u>and</u> <u>eliminated</u> . The 2 additional points may be claimed, only once, either in the year detected or in the year the illicit discharge is eliminated.
Lbmp T M D L - 08 Implement an Alternative Stormwater Offsite Pollution Reduction Program.	This program will include installation of BMPs in alternative locations, including outside the Permit Area, within the watershed shared by urban entities or urban and non-urban entities. The alternative stormwater offsite pollution reduction program shall be developed with watershed interests, such as other communities, Watershed Restoration and Protection	In the year the Alternative Stormwater Offsite Pollution Reduction Program is approved by KDHE points may be claimed. In subsequent years in which the program is maintained points may be claimed.	5 points may be claimed in the year KDHE approves the program, 4 points may be claimed for each subsequent year it remains in effect.

Kansas Permit No.: M-AR58-SU01 Page 45 of 57

F	T	······	
	Strategy (WRAPS)		
	groups and		
	Conservation Districts		
	lying outside the		
	Permit Area for the		
	joint purpose of		
	reducing pollutant		
	loads generated from		
	urban and non-urban		
	lands within the		
	shared watershed.		
	Candidate offsite		
	locations and		
	practices will be		
	consistent with		
	implementing existing		
	watershed plans that		
	identify specific		
	urban and non-urban		
· · · · · · · · · · · · · · · · · · ·	(such as agricultural)		
	BMP types and		
	locations to achieve		
	TMDLs reductions. The		
	Alternative Stormwater		
	Offsite Pollution		
	Reduction Program		
	shall be subject to		
	KDHE approval and		
	approved by KDHE prior		
	to incorporation into		
	the permittee's SMP.		
Lbmp T M D L - 09			
Implement a program to	The four litter	The fame 11	
collect and properly		The four collection	
	collection efforts	efforts must occur	2 points may
dispose of litter, on	should, but are not	in a calendar year.	be claimed for
four separate	required to, occur		any year in
occasions per calendar	seasonally, i.e.,		which four
year, within areas	winter, spring, summer		collection
where littering has	and fall. If it is		
been identified as a	unreasonable to		efforts have
problem. Such areas	collect litter in any		occurred in
may include municipal	season the required		compliance
parks, trails, rest	four collection		with the
areas, or other public	efforts may occur in		requirements
lands owned by the	either three seasons		of this BMP.
permittee.	or in a minimum of two		
F	seasons.		
	Jeasons.		
Lbmp T M D L - 10			3 points may
			be claimed for
			any year in
Establish a program to	Provide public	In the year five or	which
encourage Rainwater	education on rainwater	more residential	sufficient
Harvesting.	harvesting and design	rain barrel systems	rain
	guidance for the	or one commercial	harvesting
1			
	I Installation of rain	CISTERN are tinalin	evetome are
	installation of rain barrels, cisterns,	cistern are finally constructed and	systems are constructed or

Kansas Permit No.: M-AR58-SU01 Page 46 of 57

	raingardens and other rainwater harvesting devices. When rain barrels are utilized they must be a minimum size of 50 gallons. When raingardens are utilized they must be a minimum of 20 square feet. A rain harvesting system on a commercial setting must have adequate capacity to hold the runoff from the impervious surface for which it is designed to collect on the commercial parcel equal to that generated by a 0.1- inch rainfall event. The installation of rain barrels or rain gardens on five residential lots, or the installation of one rain harvesting system in a commercial setting shall qualify the permittee to claim points for this BMP.	become operational the points may be initially claimed and in subsequent years when at least five residential rain barrel systems or one commercial cistern remain operational points may be claimed.	<pre>maintained in operation in compliance with the requirements of this BMP.</pre>
Lbmp T M D L - 11 Construct and maintain a structural BMP to reduce loadings of sediment and nutrients, including bioretention, detention basins, porous pavement, retention ponds, media filters and any composite treatment trains of multiple BMPs	A construction project installing a structural BMP must be completed prior to awarding of points. Any individual project will be awarded points scaled on the basis of the extent of the contributing area that the BMP will control. The permittee will document maintenance of the constructed BMP in subsequent years to continue to be awarded points.	By year five of this permit, at least two structural BMP projects will be constructed and maintained. Points will be awarded in the year construction was completed and subsequent points will be awarded in the subsequent years after documentation of maintenance of the project.	<pre>4 points may be claimed for any year in which a structural BMP project is completed for a contributing area exceeding one acre. 3 points may be claimed for any year in which a structural project is completed for a contributing area under one acre. A bonus point may be awarded for a composite BMP project. 2 points may be awarded in</pre>

Kansas Permit No.: M-AR58-SU01 Page 47 of 57

			years upon documentation of ongoing maintenance of the BMPs.
Lbmp T M D L - 12			3 points may be claimed for the year in
Construct a stream bank stabilization project.	Install a minimum of 100 feet of bank stabilization at a site(s) with a history of erosion.	The installation of, the minimum 100 feet of bank stabilization must occur in the year points are claimed at a single site or at multiple sites. The sites may be on the same stream or on different streams.	which the required minimum amount of stream bank stabilization is installed, 2 points may be claimed for each subsequent year it remains in effect.

- 1. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the TMDL BMP Implementation Requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- 2. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

The permittee shall implement Best Management Practices (BMPs) to reduce to the Maximum Extent Practicable the discharge of the TMDL regulated pollutants from the MS4 to the watershed of the impaired stream(s) as listed below:

TMDL TABLE

Total Maximum Daily Loads, TMDLs, are established for waters found on the CWA Section 303d list of impaired waters. The purpose of the TMDL is to define the necessary and allowable pollutant load that may enter those impaired waters, so those waters attain a condition that fully supports all their designated uses. The TMDL then allocates portions of that allowable load among the likely point and non-point sources discharging the pollutant into the water or its watershed. Implementation of the TMDL by the NPDES and 319 programs brings about reductions in current loading from those sources through numeric goals or narrative actions to the allowable level allocated to each source.

TMDL Regulated Pollutant	Specific Impaired Stream(s) to Target
Bacteria	Big Slough
Nutrients	Big Slough
Sediment	Big Slough

The required surface water monitoring locations* and their EDMR codes are identified as follows:

	SURFACE WATER MONITORING LOCATIONS				
LOCAL SITE NAME	LOCAL ID.	LOCATION DESCRIPTION	KDHE EDMR CODE		
Upstream Maize Rd.	Upstream	Upstream at Maize Road.	UPST001A6		
Downstream 45 th St.	Downstream	Downstream at 45 th Street.	DOWN001B6		

* Note - Monitoring locations may change with KDHE approval.

B. Monitoring Requirements

1. Storm Event Monitoring: The permittee shall implement a wet weather monitoring program with the intent to assess the impact of precipitation related discharges to the stream. Sampling and analysis will normally include, instream monitoring of the main stream(s) entering and leaving the Permit Area as identified in the TMDL Table. Alternately, in some cases main stream monitoring may not be appropriate as other sources of pollutants may be introduced by point or non-point discharges and tributaries to the listed main streams, which originate within or near the Permit Area, may be monitored at a single location to characterize the water quality draining from the permit area. The permittee shall implement this monitoring program to support adaptive stormwater management and the evaluation of SMP effectiveness in reducing the discharge of pollutants from the MS4. Monitoring for the parameters listed in the Parameters table shall be conducted as required for each storm event sampled which meets the criteria specified in this section.

The storm event monitoring data for TMDLs, as required in this PART II, may be used to assist in evaluating trends in water quality. This monitoring is not necessarily intended to demonstrate compliance with the requirements of this MS4 NPDES permit.

2. Additionally, other stream monitoring, monitoring of flow within the MS4, monitoring of discharges from MS4 outfalls, monitoring to detect or locate illicit discharges, and monitoring stormwater flow within structural BMPs may be completed at the permittee's discretion to assist in management and evaluation of the BMPs and the SMP. These additional monitoring results are not required to be reported to KDHE via the eDMR reporting process.

In addition to the storm event monitoring, the permittee may want to conduct dry weather monitoring, as appropriate, to determine the effectiveness of the six minimum control measures, detect illicit discharges, or to confirm baseline water quality data. These additional monitoring results are not required to be reported to KDHE via the eDMR reporting process.

C. Monitoring Frequency and Periods Criteria

- 1. Four storm events per year per monitoring site shall be monitored. Storm event shall mean a 24-hr rain or snow melt event of greater than or equal to 0.25 inches.
- 2. Monitoring shall normally be conducted in the spring (between March 1 and June 30) and summer (between July 1 and October 31) for the parameters as appropriate based upon the impairment. It is recommended two events be monitored in the spring and two events be monitored in the summer. However, it is most important four events be monitored in each calendar year and storm event monitoring can occur in any month.

D. Parameters

TMDL Impairment	Parameter to be Monitored *	MRL **	Sample Type
Nutrients	Total Phosphorus as P (mg/l)	0.05 (mg/l)	Grab or Composite
Nutrients	Nitrate+Nitrite as N (mg/l)	0.10 (mg/l)	Grab or Composite
Nutrients	Total Kjeldahl Nitrogen (mg/l)	1 (mg/l)	Grab or Composite
Nutrients	Total Nitrogen (mg/l)		Calculate ***
Sediment	Total Suspended Solids (mg/l)	10 (mg/l)	Grab or Composite
Sediment	Turbidity (NTU)		Grab or Composite
Bacteria	E. coli (Col/100 ml or MPN)	10 (Col/100 ml or MPN)	Grab

* For a listed TMDL Regulated Pollutant in the TMDL Table, multiple parameters may be required to be monitored. In the case of Bacteria only one parameter needs to be monitored (E. coli). However, in the case of Sediment two parameters need to be monitored (Total Suspended Solids and Turbidity). In the case of Nutrients three parameters need to be monitored (Total Phosphorus, Nitrate+Nitrite as N, and, Total Kjeldahl Nitrogen). Additionally, one value needs to be calculated Total Nitrogen which equals the sum of Nitrate+Nitrite as N and Total Kjeldahl Nitrogen (the eDMR reporting process will calculate this value for the individual reporting the data).

Monitoring in impaired streams to test for TMDL pollutants, as listed in the TMDL Table does not necessarily require monitoring for all of the parameters listed in the Parameters table. For a stream, or its tributary, where monitoring is conducted, only the parameters associated with the listed TMDL Regulated Pollutant need to be monitored.

- ** Minimum Reportable Limit
- *** Total Nitrogen = Total Kjeldahl Nitrogen + Nitrate+Nitrite.

In addition, at the time of sampling, report the following:

1. Rainfall (last 24 hours) – inches	Gauge Reading
2. Stream Flow - CFS	Estimate/Reading
3. Stream Depth from a standard - Feet	Estimate/Reading
4. Stream Level (rising, falling, steady)	Describe
5. Stream Velocity (rapid, normal, still [backwater])	Describe

For storm events, grab samples for instream monitoring are to be obtained within 4 hours of rising stages on streams. Monitoring of a storm event for the purpose of complying with the stormwater monitoring and reporting requirements of this permit is not allowed if there is not at least 24 hours between this sampling storm event and the end of the previous rainfall event. If composite sampling is conducted, samples are normally collected over the course of the hydrograph and flow-weighted to provide a representative composite sample for the storm event.

E. Adaptive Management

The monitoring program may be adapted to improve the effectiveness of the SMP or if supported by additional information. It may also be supplemented or supplanted with modeling approaches to meet monitoring plan objectives. Any modifications to the monitoring program are subject to KDHE approval.

F. Documentation of Stream Monitoring Locations

The permittee, within 100 days following the effective date of this permit, shall provide KDHE maps illustrating the wet weather surface water monitoring locations and a table listing information associated with each monitoring location in a similar fashion as required by the annual reports. In some cases, KDHE has approved a rotational monitoring program where some monitoring locations are only monitored in certain years, if this is the case the table must list the years monitoring is required or alternately indicate all years. Information provided in the table shall be formatted similar to the following example:

Local Site Name	Farwell	
Local Site Identifier	C1	
Sample Location Description	On the east side of this bridge is a pedestrian walkway where a rope and bucket are lowered to the middle of the river to obtain a sample.	
KDHE EDMR Code if Known	Far2002C5	
Lat/Long Data - Decimal & Degree Format		
Latitude	42.367056°	
Longitude	-71.218089°	
Years monitoring will be conducted	2019 and 2022 (Alternate notation is all years)	

EPA has promulgated a final rule requiring regulated entities to report DMR data electronically. Also, KAR 28-16-63 requires permittees to report NPDES data in a form required by KDHE. KDHE has developed electronic reporting tools to assist permittees in complying with the EPA electronic reporting rule and KAR 28-61-63. Unless a waiver has been approved by KDHE, permittees are required to submit reports electronically via the eDMR process.

The storm event monitoring data for TMDLs, as required in this PART II, is required to be reported to KDHE via the electronic DMR (eDMR) process. Additional monitoring of streams flowing within or near the Permit Area, monitoring industrial stormwater discharges (PART III), monitoring of discharges from MS4 outfalls, or discharges from areas with BMPs may be done at the permittee's discretion to assist in management and evaluation of the BMPs (process control/monitoring) and for compliance with the SMP and/or this permit. This additional monitoring is not required to be reported via the eDMR process.

PART III. MONITORING INDUSTRIAL STORMWATER DISCHARGES:

This PART III requirement is not applicable to Phase II permittees. No action is required at this time for Monitoring Industrial Stormwater Discharges.

PART IV. PERMIT COMPLIANCE ACTIVITIES AND SCHEDULES

A. Year 2019:

The required update to the stormwater management program (SMP) document, as required in PART I B. Updated Stormwater Management Program document, should be considered in 2019 and planning initiated for allocating time and effort to complete this task to update the SMP document prior to the submission deadline in 2021.

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

Within 100 days following the effective date of this permit the permittee must submit the required information regarding the wet weather surface water monitoring locations as addressed in PART II, B, 1 Monitoring Requirements.

The Annual Report for calendar year 2018 must be submitted to KDHE between January 1 and February 28, 2019.

B. Year 2020:

Any remaining tasks necessary to complete the update of the SMP should be completed in 2020.

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The Annual Report for calendar year 2019 must be submitted to KDHE between January 1 and February 28, 2020.

C. Year 2021:

The updated SMP document must be submitted to KDHE with the 2020 Annual Report between January 1 and February 28, 2021.

The permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year beginning in 2021.

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The Annual Report for calendar year 2020 must be submitted to KDHE between January 1 and February 28, 2021.

D. Year 2022:

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year.

The Annual Report for calendar year 2021 must be submitted to KDHE between January 1 and February 28, 2022.

E. Year 2023

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year. The point total requirements increase this year.

By February 28, 2023, provide a report (in PDF format) on effectiveness of source controls and structural BMPs to attenuate pollutant discharge and achieve the measurable goals. And if the TMDL Table in PART II lists TMDL Regulated Pollutants and the permittee is required to conduct surface water monitoring of specific impaired streams, this report must also summarize water quality data from in stream monitoring sites. This report must be submitted to KDHE along with the Annual Report for 2022.

The Annual Report for calendar year 2022 must be submitted to KDHE between January 1 and February 28, 2023.

F. Year 2024

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year.

The Annual Report for calendar year 2023 must be submitted to KDHE between January 1 and February 28, 2024.

PART V. REPORTING

- A. The permittee shall submit a calendar year annual report to KDHE by February 28 of each year. The annual report shall be submitted to KDHE in the form specified by KDHE. Normally an annual report template (Basic Report) is posted on the KDHE website in the last three months of each year. The report template can be downloaded and completed. The completed annual report along with attachments or other documents which need to be submitted in association with the annual report shall all be submitted in PDF file formats to KDHE on a standard compact disk (CD) or digital versatile disk (DVD). The initial report under this permit is due February 28, 2020 for calendar year 2019. Once KDHE has implemented the KEIMS webbased system, all documents submitted will be required to be uploaded through the KEIMS program. KDHE will provide notification to the permittee when reporting via the KEIMS system is required. The annual report shall cover the activities during the previous calendar year and must include:
 - 1. Provide the status of compliance with permit conditions, an assessment of the appropriateness of the implemented Best Management Practices, progress towards achieving the statutory goal of reducing the discharge of pollutants to the maximum extent practicable (MEP), and the measurable goals with an indication of the progress toward meeting the goals for each of the six minimum control measures.

- 2. Provide results of information collected and analyzed, (for example test results, surveys, or public comments/input) during the annual reporting period. This may include monitoring data used to assess the success of best management practices with respect to reduction in pollutant discharge. Include an interpretation of the information which addresses success or failure of the portion of the program for which the information applies.
- 3. For Best Management Practices (BMPs), which are directed at reducing the discharge of TMDL regulated pollutants, provide the measurable goals of each BMP with an indication of the progress toward meeting the goals.
- 4. Provide results of information collected and analyzed, if any, during the annual reporting period, including monitoring data used to assess the success of the program at reducing the TMDL regulated pollutants.
- 5. Provide a summary of the stormwater activities that were scheduled to be undertaken during the previous calendar year and the status of these activities.
- 6. Provide a summary of the stormwater activities which are scheduled to be undertaken during the next calendar year (including an implementation schedule).
- 7. Provide a map showing changes in the permittee's Permit Area if the permit area has changed within the year.
- 8. Provide a description of significant changes in any of the BMPs.
- 9. Provide copies of any ordinances or resolutions which were updated in the last year and are associated with the SMP.
- 10. Provide a list of other parties (such as other municipalities or consultants), which are responsible for implementing any of the program areas of the Stormwater Management Program.
- B. Information and monitoring results gathered in compliance with PART II TOTAL MAXIMUM DAILY LOAD (TMDL) BEST MANAGEMENT PRACTICES AND SURFACE WATER MONITORING, must be reported in compliance with the eDMR reporting requirement as addressed in B. Monitoring Requirements, Frequency and Parameters.

STANDARD CONDITIONS FOR KANSAS WATER POLLUTION CONTROL AND NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MS4 PERMITS

1. Representative Sampling and Monitoring Report Submittals:

- A. Samples and measurements taken as required herein shall be representative of the quality of the monitored water. Test results shall be recorded for the day the samples were taken. All samples shall normally be taken at the locations designated by the permittee in the Stormwater Management Plan according to the requirements of this permit. In the event samples must be obtained from a location different than that designated in the Stormwater Management Plan the annual report shall indicate the change of location and provide the justification therefore.
- B. Monitoring results shall be recorded and reported on forms acceptable to the Division and provided in the annual report. Signed and certified copies of the annual report prepared in accordance with KAR 28-16-59, and all other reports required herein, shall be sent by U.S. mail to:

Kansas Department of Health & Environment Bureau of Water-Municipal Programs Section 1000 SW Jackson Street, Suite 420 Topeka, KS 66612-1367

2. Definitions:

A. A "grab sample" is an individual sample collected in less than 15 minutes. A "composite sample" is a combination of individual samples in which the volume of each individual sample is proportional to the flow, or the sample frequency is proportioned to the flow rate over the sample period, or the sample frequency is proportional to time.

- B. The terms "Director", "Division", and "Department" refer to the Director, Division of Environment, Kansas Department of Health and Environment, respectively.
- C. "Severe property damage" means substantial physical damage to property, damage to the treatment/control facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a diversion.
- 3. Duty to Mitigate: The permittee shall take all reasonable steps to minimize or prevent any damage to the environment or hazard to human health from any discharge in violation of this permit.
- 4. Test Procedures: All analyses required by this permit shall conform to the requirements of 40 CFR Part 136, unless otherwise specified, and shall be conducted in a laboratory accredited by the Department. For each measurement or sample, the permittee shall record the exact place, date, and time of measuring/sampling; the date and time of the analyses, the analytical techniques or methods used, minimum detection or reportable level, and the individual(s) who performed the measuring/sampling and analysis and, the results. If the permittee monitors any pollutant at the location(s) designated herein more frequently than required by this permit, using approved procedures, the results shall be included in the Monitoring Report form required in 1.B. above. Such increased frequencies shall also be indicated.
- 5. Change in Discharge: All stormwater discharges shall be in compliance with the conditions of the permit. Modification or expansion of the storm sewer system is allowed. All new storm sewer segments and outfalls constructed after the effective date of the permit, which are located within the permit area, are authorized under the permit and must comply with the permit conditions.
- 6. Proper Operations and Maintenance: The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the requirements of this permit and Kansas and Federal law.

7. Incident Reporting: The permittee shall report any unanticipated significant incidents which would be expected to result in non-compliance with the permit requirements within 24 hours from the time the permittee became aware of the incident. A written submission shall be provided within 5 days of the time the permittee became aware of the incident. The written submission shall contain a description of the noncompliance and its cause, the period of noncompliance, including exact dates and times; and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.

For an anticipated incident or any planned changes or activities in the permitted control/treatment facility that may result in noncompliance with the permit requirements, the permittee shall submit written notice, if possible, at least ten days before the date of the event.

- 8. Removed Substances: Solids, sludges, debris, or other pollutants removed in the course of control/treatment of stormwater shall be utilized or disposed of in a manner acceptable to the Division.
- 9. Right of Entry: The permittee shall allow authorized representatives of the Division of Environment or the Environmental Protection Agency upon the presentation of credentials, to enter upon the permittee's premises where a stormwater discharge or source is located, or in which are located any records required by this permit, and at reasonable times, to have access to and copy any records required by this permit, to inspect any facilities, monitoring equipment or monitoring method required in this permit, and to sample any stormwater discharges from or influents into the stormwater control/treatment facilities.
- 10. Transfer of Ownership: The permittee shall notify the succeeding owner or controlling person of the existence of this permit by certified letter, a copy of which shall be forwarded to the Division. The succeeding owner shall secure a new permit. This permit is not transferable to any person except after notice and approval by the Director. The Director may require modification or revocation and reissuance of the permit to change the name of the permittee and incorporate such other requirements as may be necessary.
- 11. Records Retention: Unless otherwise specified, all records and information resulting from the monitoring activities required by this permit, including all records of analyses and calibration and maintenance of instruments and recordings from continuous monitoring instruments, shall be retained for a minimum of 3 years, or longer if requested by the Division.
- 12. Availability of Records: Except for data determined to be confidential under 33 USC Section 1318, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Department. Treated and raw stormwater data shall not be considered confidential. Knowingly making any false statement on any such report or tampering with equipment to falsify data may result in the imposition of criminal penalties as provided for in 33 USC Section 1319 and KSA 65-170c.
- 13. Permit Modifications and Terminations: As provided by KAR 28-16-62, after notice and opportunity for a hearing, this permit may be modified, suspended or revoked or terminated in whole or in part during its term for cause as provided, but not limited to those set forth in KAR 28-16-62 and KAR 28-16-28b through g. The permittee shall furnish to the Director, within a reasonable amount of time, any information which the Director may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The permittee shall also furnish upon request, copies of all records required to be kept by this permit. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.
- 14. Administrative, Civil and Criminal Liability: The permittee shall comply with all requirements of this permit. Nothing in this permit shall be construed to relieve the permittee from administrative, civil or criminal penalties for noncompliance as provided for in KSA 65-161 et seq., and 33 USC Section 1319.
- 15. Oil and Hazardous Substance Liability: Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities or penalties to which the permittee is or may be subject to under 33 USC Section 1321 or KSA 65-164 et seq. A permittee shall promptly notify the Division by telephone upon discovering crude oil or any petroleum derivative in its storm sewer system or stormwater control/treatment facilities.

- 16. Property Rights: The issuance of this permit does not convey any property rights in either real or personal property, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights nor any infringements of or violation of federal, state or local laws or regulations.
- 17. Severability: The provisions of this permit are severable. If any provision of this permit or any circumstance is held invalid, the application of such provision to other circumstances and the remainder of the permit shall not be affected thereby.
- 18. Removal from Service: The permittee shall inform the Division at least three months before any control/treatment unit, or any other part of the control/treatment facility permitted by this permit is to be removed from service and shall make arrangements acceptable to the Division to decommission the facility or part of the facility being removed from service such that the public health and waters of the state are protected.
- 19. Duty to Reapply: A permit holder wishing to continue any activity regulated by this permit after the expiration date, must apply for a new permit at least 180 days prior to expiration of the permit.